



## Very refined, very Varion

### Varion "5.1 Set"

The Varion is among the most flexible home cinema sets on the market today. Mount the speakers directly onto your television, on table or speaker stands or directly to the wall. In spite of its elegant, easily-placed form, the Varion knows how to deliver immersive surround sound for a thrilling home cinema experience.

#### Highlights:

- Super slim high performance home cinema speakers
- Can be wall mounted, placed on table stands, speaker stands or optional TV brackets
- 5 identical 2-way speakers with 7 drivers each create a powerful & harmonious surround soundstage
- 6 midrange drivers per speaker ensure a high degree of speech intelligibility, even at low volumes
- Matching slim but powerful 100 watt subwoofer can be unobtrusively placed

## Included components

- 2 x Satellite Speaker CS 75 FCR (pcs.)
- 3 x Satellite Speaker CS 75 FCR (pcs.)
- 1 x Center Wedge CS 75 CW (pcs.)
- 1 x Mono-Subwoofer US 2106/1 SW

## Specifications

### Satellite Speaker CS 75 FCR (pcs.):

<b>Speaker</b>	Acoustic principle	2-Way-System
	Enclosure type	Closed
	Continuous power handling (IEC - Long Term)	80 Watt
	Peak power capacity (IEC - Short Term)	160 Watt
	Sensitivity (2.83 V / 1 m)	89 dB
	Minimum amplifier output power recommended	20 Watt
	Maximum sound pressure level	105 dB/1m
	Impedance	4 - 8 Ohm
	Frequency range from/to	200 - 20000 Hz
	Crossover frequency internal switch	4400 Hz
	Crossover frequency to Woofer (recommended)	150 - 200 Hz
	Miscellaneous	Requires little power to achieve high levels
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	19.00 mm
	Tweeter (material)	Fabric
	Midrange driver (number per enclosure)	6
	Midrange driver (diameter)	55.00 mm
	Midrange driver (material)	Coated cellulose
	Miscellaneous	Drivers with high efficiency rating
	Enclosure material	Structural synthetic
	Enclosure surface	Matte lacquer
	Diameter of the stand screw threads	6.00 mm
	Keyhole plate mounted	Yes
	Miscellaneous	With resonance-damping thick enclosure walls
	Terminal clamps	Yes
	Maximum cable diameter	2.50 mm
	Suitable for AV receiver	Yes
<b>Dimensions</b>	Depth	6.50 cm
	Width	7.00 cm

Height	50.20 cm
Weight	1.20 kg

#### Mono-Subwoofer US 2106/1 SW:

<b>Speaker</b>	Acoustic principle	1-Way-System
	Downfire	Yes
	Enclosure type	Bass reflex
	Sensitivity (2.83 V / 1 m)	89 dB
	Maximum sound pressure level	106 dB/1m
	Impedance	4 - 8 Ohm Ohm
	Frequency range from/to	43 - 200 Hz Hz
	Woofer (number per enclosure)	1
	Woofer (diameter)	160.00 mm
	Woofer (material)	Cellulose, coated
	Miscellaneous	Optimised with Klippel®-measurement method
	Enclosure material	MDF
	Enclosure surface	Foil / high-gloss lacquer
	Equalisation openings	2
	Equalisation openings (pos.)	bottom
	Removable front cover	Yes
	Integrated stand	Yes
	Diameter of the stand screw threads	6.00 mm
	Miscellaneous	Robust MDF housing with internal reinforcements
	Suitable for AV receiver	Yes
<b>Connections</b>	Cinch input	1
<b>Electronics</b>	Lowest frequency (-3 dB)	43 Hz
	Bass boost/EQ	Yes
	Input gain adjustment	Yes
	Level control	Yes
	Phase control	Yes
	Amplifier technology	Class-D
	Amplifier configuration	1.0
	Amplifier channels	1
	Power output capacity impulse (peak) Bass	100 W
	Power output capacity sinus (RMS) Bass	80 W
	Power supply voltage	230 Volt volts
	Standby-Function	Yes
	Standby-Power consumption	0.40 watt
	Maximum power consumption	100 watt

	Mains lead fixed	Yes
	Safety class	2
	Storage for settings when disconnected	Yes
	Automatic on/off	Yes
	Miscellaneous	High-performance adapter for stable power supply
<b>Dimensions</b>	Depth	28.00 cm
	Width	28.00 cm
	Height	38.50 cm
	Weight	7.80 kg
	Miscellaneous	Absorber pads included in delivery