

# EH461

Full HD 1080p, Bright and Powerful

- Bright Full HD 1080p projector - 5000 ANSI Lumens
- Ultimate Control - Crestron, Extron, AMX, PJ-Link and Telnet LAN commands
- Easy connectivity – 2x HDMI + MHL, RJ45, USB Power, 12V Trigger
- Quality audio featuring 10W speaker



Give hassle free and cable free presentations from a USB stick using the built-in photo and document viewer. You can even give presentations wirelessly from a mobile device using the optional wireless dongle.

This Full HD 1080p projector is ideal for meetings and classroom. Boasting ultra-bright images for optimum visibility and a wide range of inputs allow you to effortlessly connect to devices such as computers and tablets. Additionally a built-in 10W speaker enables clear and loud audio.

For ultimate control, the projector comes with RJ45 connection allowing you to monitor and control your network in multiple rooms.

Display/image

Display technology	DLP
Resolution	1080p Full HD (1920x1080)
Brightness	5.000 lumens
Contrast ratio	20.000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - horizontal	25
Keystone correction - vertical	30
Horizontal scan rate	15.375 ~ 91.146Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	75%
Screen size	0.96m - 5.3m (37.98in - 208.5in)

Lamp info

Light source	Lamp
Lamp watts	285
Lamp life (hours)	2500 (Bright), 4500 (Dynamic), 3500 (Eco), 4500 (Eco+)

Optical

Throw ratio	1.22:1 - 1.46:1
Projection distance (m)	1.23m - 5.63m
Zoom	1.2
Zoom type	Manual
Focal length (mm)	16.87 ~ 21.87
Native offset	115%

Connectivity

Connections	<b>Inputs</b> 1 x HDMI 1.4a 3D support, 1 x HDMI 1.4a 3D support + MHL, 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A reader <b>Outputs</b> 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm <b>Control</b> 1 x USB-A wireless, 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x mini USB mouse/service
-------------	--

General

Noise level (typical)	29dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Operating conditions	
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	10W
In the box	AC power cord, remote control, 2x AA batteries, basic user manual

Networking

LAN - control	Yes
LAN - display	Yes
LAN - wireless networking	Yes

Power

Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (max)	350W

Weight and dimensions

Net weight	2.95kg
Dimensions (W x D x H) (mm)	345 x 216 x 109

