



Turn off the light!

Consono 35 Complete Power Edition

Our bestseller is now also available with an extra powerful T 10 subwoofer. For those who are looking for a complete, ready-to-play home cinema system with small satellites but a powerful Teufel bass.

Highlights:

- Ready-to-play 5.1 complete system incl. AV receiver, micro Hi-Fi satellites and powerful subwoofer
- Powerful, detailed playback for music, movies & games
- Stylish satellites with sturdy metal grilles & elegant chrome ring
- 5 identical 2-way speakers, each with 2 mid-range drivers for realistic, powerful surround sound
- CoreStation is an ultra-compact AV receiver for discrete, silent operation

Included components

- 1 x Centre Speaker CS 35 C Mk3
- 4 x Satellite-Speaker CS 35 FCR Mk3
- 1 x T 10 Subwoofer
- 1 x CoreStation
- 1 x power cable
- 1 x Remote Control for Corestation
- 1 x 30m Speaker Cable 1.0mm² - C1030S
- 1 x HDMI-Cable 1.4 1.5m - C1515V

Specifications

CoreStation:

Connections	Bluetooth aptX	Yes
	Bluetooth	Yes
	Bluetooth	4.0 with aptX
	Digital inputs coaxial	1
	Digital inputs optical	2
	Cinch input	1
	Stereo jack 3.5mm - in	2
	High level speaker outputs	5
	Headphone output 3,5mm	1
	Video inputs- HDMI	4
	HDMI Version	1.4a (3D)
	Video outputs - HDMI	1
	Video outputs - HDMI	Yes
	HDMI Version	1.4a (3D)
	Miscellaneous	USB port for software updates
Playback	Dolby Digital	Yes
	DTS	Yes
	Dolby Pro Logic II	Yes
	Dolby Pro Logic II	Music, movies
Radio	Radio present	Yes
	Channel memory slot - FM	30
	FM - UKW	Yes
Electronics	Amplifier technology	Class-D
	Amplifier configuration	5.0
	Amplifier channels	5
	Power output capacity impulse (peak) Satellite	100 W
	Power output capacity sinus (RMS) Satellite	80 W
	Performance measured by (Ohm)	4

	Miscellaneous	30 Watt/Rear
	Power supply voltage	230 Volt volts
	Standby-Function	Yes
	Standby-Power consumption	0.40 watt
	Maximum power consumption	500 watt
	Mains cable - IEC connector (non-heating device)	Yes
	Safety class	2
	Storage for settings when disconnected	Yes
	Miscellaneous	Automatic off
	Integrated DSP	Yes
	Integrated DD/dts/PLII-Decoder	Yes
	Remote control	Radio
	Materials	Aluminium
	Presets	Yes
Dimensions	Depth	24.00 cm
	Width	30.80 cm
	Height	6.30 cm
	Weight	3.40 kg

Satellite-Speaker CS 35 FCR Mk3:

Speaker	Acoustic principle	2-Way-System
	Enclosure type	Closed
	Continuous power handling (IEC - Long Term)	80 Watt
	Peak power capacity (IEC - Short Term)	160 Watt
	Sensitivity (2.83 V / 1 m)	88 dB
	Minimum amplifier output power recommended	10 Watt
	Maximum sound pressure level	105 dB/1m
	Impedance	4 - 8 Ohm
	Frequency range from/to	150 - 20000 Hz
	Crossover frequency internal switch	3400 Hz
	Crossover frequency to Woofer (recommended)	150 - 180 Hz
	Miscellaneous	Neutral tuning
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	19.00 mm
	Tweeter (material)	Silk
	Midrange driver (number per enclosure)	2
	Midrange driver (diameter)	80.00 mm
	Midrange driver (material)	Cellulose, coated
	Miscellaneous	High excursion drivers
	Enclosure material	Synthetic
	Enclosure surface	Impact-resistant lacquer, matte

	Net internal volume	1.20 Litres
	Diameter of the stand screw threads	6.00 mm
	Keyhole plate mounted	Yes
	Miscellaneous	Strong walls minimize resonances
	Maximum cable diameter	2.50 mm
	Suitable for AV receiver	Yes
	Miscellaneous	requires little power for high levels
Dimensions	Depth	9.50 cm
	Width	10.00 cm
	Height	22.60 cm
	Weight	1.25 kg

Centre Speaker CS 35 C Mk3:

Speaker	Acoustic principle	2-Way-System
	Enclosure type	Closed
	Continuous power handling (IEC - Long Term)	80 Watt
	Peak power capacity (IEC - Short Term)	160 Watt
	Sensitivity (2.83 V / 1 m)	88 dB
	Minimum amplifier output power recommended	10 Watt
	Maximum sound pressure level	105 dB/1m
	Impedance	4 - 8 Ohm
	Frequency range from/to	150 - 20000 Hz
	Crossover frequency internal switch	3400 Hz
	Crossover frequency to Woofer (recommended)	150 - 180 Hz
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	19.00 mm
	Tweeter (material)	silk
	Midrange driver (number per enclosure)	2
	Midrange driver (diameter)	80.00 mm
	Midrange driver (material)	coated cellulose
	Miscellaneous	high excursion driver
	Enclosure material	structure - synthetic
	Enclosure surface	impact-resistant lacquer, matte
	Net internal volume	1.20 Litres
	Diameter of the stand screw threads	6.00 mm
	Keyhole plate mounted	Yes
	Miscellaneous	strong walls minimize resonances
	Maximum cable diameter	2.50 mm
	Suitable for AV receiver	Yes
	Miscellaneous	requires little power for high

Dimensions	Depth	levels 9.50 cm
	Width	22.60 cm
	Height	10.00 cm
	Weight	1.25 kg

T 10 Subwoofer:

Speaker	Acoustic principle	1-Way-System
	Downfire	Yes
	Frontfire	Yes
	Enclosure type	Bass reflex
	Maximum sound pressure level	115 dB/1m
	Frequency range from/to	37 - 200 Hz Hz
	Woofer (number per enclosure)	1
	Woofer (diameter)	250.00 mm
	Woofer (material)	Aluminium
	Enclosure material	MDF
	Enclosure surface	Matte coated
	Equalisation openings	1
	Integrated stand	Yes
	Miscellaneous	Reflection channel in DPU technology avoids flow noises, stable MDF housing structure with internal bracing
Connections	Suitable for AV receiver	Yes
	Cinch input	1
Electronics	Lowest frequency (-3 dB)	33 Hz
	Bass boost/EQ	Yes
	Input gain adjustment	Yes
	Level control	Yes
	Phase control	Yes
	Miscellaneous	Can be used either front- or down-firing
	Amplifier technology	Class-D
	Amplifier configuration	1.0
	Amplifier channels	1
	Power output capacity impulse (peak) Bass	150 W
	Power supply voltage	230 Volt volts
	Standby-Function	Yes
	Standby-Power consumption	1 watt
	Maximum power consumption	150 watt
	Mains lead fixed	Yes
	Safety class	2

	Fuse	Yes
	Storage for settings when disconnected	Yes
	Automatic on/off	Yes
	Miscellaneous	Wireless subwoofer module integrated (subwoofer with compatible feeders can be controlled wirelessly)
Dimensions	Depth	38.00 cm
	Width	35.10 cm
	Height	48.30 cm
	Weight	15.60 kg