

# MC-TW3506

## Interactive Ultra Short Throw 3LCD Projector



**PJLink™**

**CRESTRON**

**HDMI™**  
HIGH DEFINITION MULTIMEDIA INTERFACE

**AMX**

**3LCD**

**Introducing our interactive 3LCD MC-TW3506 projector, which combines all our technical expertise with our market leading knowledge.**

This easy to install, interactive 3LCD ultra short throw projector gives a brightness of 3,700 ANSI lumens. The compact, lightweight design, integrates a powerful 16,000:1 contrast ratio with WXGA resolution, providing clarity on images even within very bright / light environments.

### Key Features:

WXGA 1280 x 800 resolution

3,700 ANSI lumens white / colour output

16000:1 contrast ratio

Images up to 100" diagonal

Digital zoom and powered focus

Starboard Interactive Software included

3 year warranty\*

Please note: Content, technical specifications and images are subject to change.


\*For education and extended warranties please contact your local dealer.

# MC-TW3506 3LCD Projector

## Technical Specifications

Panel Size	3LCD 15mm (0.59")
Panel Structure	3LCD
Light Source	Lamp
Resolution	WXGA (1280 x 800)
Light Output (Brightness) ANSI Lumens	3700 (Normal), 3034 (Eco), 2516 (Eco-2)
Contrast Ratio	16000:1
Light Source Life (Hours)	4,000
Number of colours	16.7 million colours
Lens	Built-in
Lens Zoom	Digital Zoom x 1.35
Lens Focus	Powered Focus
Projection Lens F Number	1.8
Focus Distance	0.41 – 0.69m (centre of glass to screen)
Distance to Width Ratio/Throw Ratio (:1)	0.3
Diagonal Display Size	60 – 100"
Installation	Ceiling, Tabletop, Rear
Speakers	16W mono
Digital Keystone Correction (Degrees)	Horizontal $\pm 5^\circ$ , Vertical: $\pm 5^\circ$
Picture Modes	Normal, Cinema, Dynamic, Board (Black), Board (Green), Whiteboard, Daytime, Photo, DICOM SIM.
Picture Adjustments	ASPECT selection (Normal/4:3/16:9/16:10/14:9), Perfect Fit (4 corners and 4 sides), Frame Lock (Data signal with vertical frequency of 49 to 51Hz, 59 to 61Hz), HDCR, Image blank by RS232C/Remote control, Magnify 4 times, Mirror reverse image, Up-side down image
Operating Features	Keystone V/H, PerfectFit, Standby audio, Audio pass through, Cloning function, Easy schedule setting, Auto power on.
Network Features	Keystone V/H, PerfectFit, StandBy Audio, Audio pass through, Cloning function, Easy schedule setting, Auto-Calibration, Finger touch (Optional), Multi-Display (up to 2 projectors), PC-Less interactive, Driver-less
Security Features	Password/Myscreen Password, Pin Lock, Key Lock
On Screen Display Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Arabic, Persian, Czech, Danish, Hungarian, Romanian, Slovenian, Croatian, Greek, Lithuanian, Estonian, Latvian, Thai, Portuguese (Brazil), Indonesian, Vietnamese, Hebrew

Digital Input	HDMI x 2 (HDCP compliant, HDMI 1 shared with MHL)
Analogue Input	15-pin Mini-D-Sub x 2, RCA Jack x 1
Video Output	15 pin Mini D-Sub x 1
Audio Input	3.5mm Stereo Mini Jack x 2, RCA Jack (L/R) x 1
Audio Output	3.5mm Stereo Mini Jack x 1
RS-232C Control	1 x 9-pin D-Sub
Wireless LAN	USB-WL-5GM wireless adapter (optional)
Wired LAN	RJ45 connector x 1
USB- Type-A	USB Type A x 2 (PC less presentation or wireless adapter), USB type A for FT-01BM x 1 (for power supply of the FT-01BM)
USB- Type-B	USB Type B x 1 (USB display, USB mouse control or interactivity connection for PC)
Power Supply	AC 100V – 120V / AC 220V – 240V (50/60Hz)
Operating Power Consumption	Normal 360W / Eco-1 320W / Eco-2 280W
Standby Power Consumption	Less than 0.35W
Weight	4.6Kg
Dimensions (W x H x D)	382 x 141 x 362mm
Noise (Normal)	37dB (Normal), 32dB (Eco), 28dB (Eco 2)
Filter Life (Hours)	4,000 Hours
Certification	CE Marking: EN61000-3-2, EN61000-3-3, EN55032 (Class A), EN55024 (EMC Directive), EN60950-1 (Low Voltage Directive), WEEE/RoHS compliant
Computer	IBM Compatible VGA, SVGA, XGA, WXGA, WXGA+/SXGA/SXGA+/WSXGA+/UXGA/HD (Compressed), MAC16"
Video	525i (480i), 525p (480p), 625i (576i), 625p (576p), 1125i (1080i@50/60), 750p (720p@50/60), 1125p (1080p@50/60)
Supplied Accessories	Power Cable (4.5m) x1, Computer Cable (5.0m) x1, USB Cable (5m) x1, IR Remote Control Unit x1, AA Batteries x2, Application CD (for network, etc.) x1, CD User Manual x1, Concise User Manual x1, Application DVD (for interactive model) x1, Security Label x1, Adapter Cover x1, Cable Cover x1, Interactive Pen x2, Pen Tip x4, AAA Batteries x4
Optional Accessories	USB wireless adapter USB-WL-5GM, Wall mount unit: HAS-WM03M, HAS-WM05M (Low ceiling wall mount), TT-03 Table Top Kit, HAS-WB01 (XGA mount adapter), HAS-WB02 (WXGA mount adapter), Finger Touch Unit FT-01BM, Interactive Pen I-PEN4M
Filter/Light Source	UX37191 / DT01411M
Remote Control	HL03033
Projector/ Light Source Warranty	3 years / 3 years or 6,000 hours which ever comes first (for education and extended warranties please contact your local dealer)



Dealer Stamp

**maxell**  
Within the Future

Maxell Limited  
Whitebrook Park, Lower Cookham Road,  
Maidenhead, Berkshire SL6 8YA,  
Tel: +44 (0)1628 585 000 / Fax: +44 (0)1628 585 163  
www.maxelldisplay.com