# IN112v

Unbelievable low price. Unbeatable value. Part #: IN112v

Confidently beam your content with the big power and unbeatable value of the InFocus IN112v SVGA projector. This projector is easy to buy and built to perform with high brightness, high contrast ratio and BrilliantColor technology. A compact design and light weight make it as easy to move around as it is to install.

## **Key Features**

- SVGA (800 x 600) resolution
- HDMI connectivity
- 3500 lumens
- 10000 hour lamp life in Dynamic Mode
- High 17000:1 contrast ratio
- Display 3D content from Blu-ray, PCs and more
- Compact design and weighs only 5.18 lbs.
- Accurate and vivid color reproduction with BrilliantColor™ technology





# High Brightness and High Contrast

The image quality of these projectors does not disappoint. Up to 3500 lumens mean bright, clear images with the lights on and the 17000:1 contrast ratio adds sharpness with darker blacks and whiter whites. Preset modes give you the best image quality on a beige wall, whiteboard, blackboard or other surface.

## **Eco Blanking**

Instantly dim the screen to divert your audience's attention onto you with the Eco Blanking feature on the remote control. Activate when the projector isn't being used and lower the lamp's power usage down to 30%. This saves energy and significantly extends the life of the lamp, which saves you money.

# **3D Ready**

The IN112v supports multiple forms of 3D – including HDMI, Blu-Ray, 3D broadcasting, video games and PC connectivity. All your audience needs are 144Hz DLP Link 3D glasses (not included) to seamlessly synchronize with the image for an awesome 3D experience..

## Low Total Cost of Ownership

Our customers benefit from an affordable price, lamps that can last up to an amazing 10,000 hours, and no filters to replace. A



# Specifications\*

Aspect Ratio43Aspect Ratio Canguability49Aspect Ratio Canguability10Projection Distance – Minimum1Projection Distance – Maximum20Image Size – Maximum29 inProjection Offset5%Connectors – InputsHDN1 14, Composite video, Svideo, S.5mn PC audo, VGA 24Connectors – Outputs35mn audio output, VGAAudible Noise – Eco Mode42 dBA at O'F / 178'CAudible Noise – Eco Mode42 dBA at O'F / 178'CAudible Noise – Eco Mode420 dBA at O'F / 178'CAudible Noise – Eco Mode90 erord, Remote, VGA cable, Documentation10kUgd AccessoriesPower cord, Remote, VGA cable, Documentation20 spopt108D g) 144 Hz via HDMI, DLP Link 3D glasses requiredProduct Warranty6 monthsAccessories Warranty0 dodysComputer Compatibility9 C, MacComputer Compatibility9 C, MacAmer LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Standard Lens –	Projector	IN112v
Beeking Machinang     WUKA (2002, 1200)       Dipplay Bechnology     IDF       Obergan Schwards Compatibility     INSC, PAL SEXAM, 4801, 4809, 576, 750, 7200/50, 1200/50, 10800/50, 10800/54, 10500/50,       Speakers     Mino 2/W X I       Lamp Briphtness     3.500 Jumers       Lamp Drow     Speakers       Lamp Drow     259W       Lamp Power     Speakers       Lamp Power     Speakers       Contrast Ratio     SPUAMP 089       Contrast Ratio     107 Dillon       Contrast Ratio     107 Dillon       San Frequency - Mericantal     15 KHz       San Frequency - Mericantal     107 Billon       San Frequency - Mericantal     108 KHz       San Frequency - Mericantal	Resolution – Native	SVGA (800 × 600)
Display EditionDisplay intermediateVerder Standar CompatibilityResider, CAM, SEGN, SEG	Resolution – Maximum	
NTSC, PAL SECAM 480, 480, 480, 578, 578, 720p/50, 720p/50, 1980/40, 1980/40, 1980/44, 1980p/50       Yorke Standard Compatibility     NTSC, PAL SECAM 480, 480p, 578, 576, 720p/50, 720p/50, 1980/40, 1980/44, 1980p/50       Spacker     Moro 2W x 1       Lamo Briphness     J500 Inoms       Lamo Briphness     J500 Inoms       Lamo Pover     2000 Inoms       Lamo Pover     Sold Name       Barbacement Lamo     Space All       Oxool 1     Space All       Number of Code     Space All       Number of Code     Space All       Sona Fraguency - Horizontal     KHz       Sona Fraguency - Horizontal     Space All       Agrees Ratio Compatibility     ES, 18-10       Projection Distance - Mainum     Im       Projection Distance - Mainum     Im       Projection Distance - Mainum     Space All       Projection Distance - Mainum     Space All       Optication Stance - Mainum     Space All       Optication Stance - Mainum     Space All       Optication Stance - Mainum     Space All     Space All       Optication Stance - Mainum     Space All     Space All     Space All	Display Technology	
Jump Brightness     3,500 lumens       Lamp Irk     5,000 hours       Lamp Power     25%W       Lamp Power     500 hours       Lamp Power     50 Mode       Brightness     15W       Reglacement Lamp     SPL-AMP-089       Contrast Ratio     17,000-1       Color Wheel     5 segment, 2x speed       Number of Colors     107 Philon       Scan Frequency - Horizontal     15 KHz       Scan Frequency - Vertical     24 KHz       Aspect Ratio     43       Aspect Ratio Compatibility     169, 1610       Projection Distance - Maxinum     1m       Projection Distance - Maxinum     1m       Projection Distance - Maxinum     20 Sim axial zoom and focus       Image Size - Maximum     299 in       Projection Distance - Maxinum     3mm axial zoom and focus       Sima axial zoom and focus     35mm axial zoom focus       Connectors - Dupts     JBMI H14. Composite video. Sivideo. 35mm PC audio. VGA x2       Connectors - Dupts     3mm axial zoom and focus       Sima axial zoom and focus     Sima axial zoom and focus       Landble Noise - Eco M		
Lang LieS000 hoursLang Power25WLang Power Foc Mode15WReplacement LangSPLAMPA08Contrast RatioSegment LangContrast RatioSegment LangContrast RatioSegment LangContrast RatioSegment LangSam Frequency - Vertical15 MbSam Frequency - Vertical16 MbAppet RatinManual Contrast RatioPojection Bizance - Maximum16 MaPojection Distance - Maximum18 MaPojection Distance - Maximum19 MaPojection Distance - M	Speakers	Mono 2W x 1
Lamp Power25WLamp Power19WLamp Rower19WLamp Rower19WContrast Raine170001Contrast Raine170001Contrast Raine107 billionScan Frequency - Horizontal107 billionScan Frequency - Horizontal15 KHzScan Frequency - Vertical424 KHzAspect Raine Compatibility169, 1610Projection Distance - Maximum12 mProjection Distance - Maximum12 mProjection Distance - Maximum29 inProjection Distance - Maximum29 inProjection Distance - Maximum29 inProjection Offere15%Connectors - Inputs35m maximo autio autio utur, VGAConnectors - Dutputs35m maximo autio autor, VGA x2Connectors - Dutputs35m maximo autio autor, VGAAudible Noise - Eco Made42 BAA at 07 / 178°CAudible Noise - Eco Made23 BAA at 07 / 178°CAudible Noise - Eco Made90 daysCompater Size Maximum90 daysCompater Size Maximum90 daysCompater Size Maximum90 daysCompater Size Maximum90 daysCompater Size Maximum15%Contrast Compater Size Maximum90 daysCompater Size Maximum90 daysCompater Size Maximum90 daysCompater Size Maximum90 daysCompater Size Maximum15%Contrast Compater Size Maximum90 daysContrast Compater Size Maximum90 daysContrast Compater Si	Lamp Brightness	3,500 lumens
Lamp Power – Eco Mode191WReplacement LampSP LAMP 089Contrast RainSP LAMP 089Contrast RainSegment, 2x speedNumber of ColarsSegment, 2x speedSoan Frequency – Horizontal15 KHzSoan Frequency – Vertical24 KHzAppect RainAgaAppect RainBis 100Projection Distance – Minimum1mProjection Distance – Manimum1mProjection Distance – Manimum1mProjection Distance – Manimum1mProjection Distance – Manimum2mProjection Distance – Manimum1mProjection Distance – Manimum1mProjection Distance – Manimum1mProjection Distance – Manimum1mProjection Distance – Manimum2mProjection Distance – Manimum1mProjection Distance – Manimum1mProjection Distance – Manimum1mProjection Distance – Manimum2mProjection Distance – Manimum1mProjection Distance – Manimum2mProjection Distance – Manimum1mProjection Distance – Manimum1mDistan Zanom1mPro	Lamp Life	5,000 hours
Replacement Lamp     SPLAMP-089       Contrast Ratio     17000:1       Contrast Ratio     17000:1       Contrast Ratio     107 bilion       Contrast Ratio     107 bilion       Scan Frequency - Horizontal     15 KHz       Scan Frequency - Vertical     24 KHz       Aspect Ratio     4.3       Aspect Ratio     16.9, 16.10       Projection Distance - Minium     1m       Projection Distance - Maximum     29 in       Projection Distance - Maximum     29 in       Projection Offset     15%       Connectors - Inputs     HDM 14, Composite video, Svideo, 3.5mm PC audio, VGA x2       Connectors - Outputs     3.5mm audio output, VGA       Audible Noise - Eco Mode     4.29 dBA at 07 / 178°C       Condextrise     90 day       Product Warranty     10909 (EdM 42 via HDM, DLP Link 30 glasses required       Product Warranty     90 days       Computer Compatibility     90 days       Construct Support     90 days       Construct Support     90 days       Construct Support     90 days       Construct Support     90 days	Lamp Power	225W
Contrast Raio70001Color Whell6 segment, 2x speedSoumer of Colors107 billionSoan Frequency - Horizontal15 KH2San Frequency - Vertical43 KH2Aspect Raio Compatibility63, 610Projection Distance - Minium1 mProjection Distance - Minium12 mItanse Size - Maximum99 InProjection Offsence - Minium99 InConnectors - Inputs35mm audia output, VGAConnectors - Inputs99 InAudible Noise4.20 BA at OF / 1/38'CAudible Noise4.20 BA at OF / 1/38'CAudible Noise4.20 BA at OF / 1/38'CAudible Noise4.20 BA at OF / 1/38'CInputs90 Jage 144 Via HDM, DLP Link 3D glasses requiredAudible Noise90 Jage 144 Via HDM, DLP Link 3D glasses requiredAccessories Warranty90 Jage 144 Via HDM, DLP Link 3D glasses requiredOreating Conditions10 Jage 5a O HUN, Janker, Anstein, Anstein, Anstein, Partis, P	Lamp Power – Eco Mode	191W
Chlor     Mendel     6 segment, 2x spaed       Number of Colors     107 bilon     107 bilon       Scan Froquency – Horizontal     15 KHz       Scan Froquency – Vertical     24 KHz       Aspect Ratio     43       Aspect Ratio     105, 15:10       Projection Distance – Minimum     1m       Projection Distance – Maximum     29 in       Distance – Maximum     29 in       Projection Offset     15%       Connectors – Inputs     Monul zoom and focus       Projection Offset     35/m madio output; VGA       Audible Noise – Eco Mode     32 dBA at 07 / 1/36°C       Audible Noise – Eco Mode     32 dBA at 07 / 1/36°C       Included Accessories     1040/p 414 via HDML, DLP Link 3D glasses mquired       Product Warranty     1040/p 444 riv ia HDML, DLP Link 3D glasses mquired       Product Warranty     1040/p 444 riv ia HDML, DLP Link 3D glasses mquired       Computer Compatibility     9C days       Computer Compatibility     PC, Mac       Computer Compatibility     PC, Mac       Computer Compatibility     PC, Mac       Computer Compatibility     PC, Mac	Replacement Lamp	SP-LAMP-089
Number of Colors107 billingScan Frequency - Horizontal24 KHzScan Frequency - Vertical24 KHzAppet Ratio69, 1600Projection Distance - Minimum1mProjection Distance - Minimum1mProjection Distance - Maximum29 inIrans TypeManual zoom and focusIransg Size - Maximum29 inProjection Offset15%Connectors - InputsHDMI 14, Composite video, Svideo, 35mm PC audio, VGA x2Connectors - Outputs35m audio output, VGAAudibi Noise< 32 dBA at OF / 178'C	Contrast Ratio	17,000:1
Scan Frequency - Horizontal     15 KH2       Scan Frequency - Vertical     24 KH2       Aspect Ratio Compatibility     163, 1610       Projection Distance - Minimum     1m       Projection Distance - Maximum     12 m       Lans Type     Manual zoom and focus       Image Size - Maximum     199 in       Projection Distance - Minimum     15%       Connectors - Inputs     HDM 14, Composite video, S-video, 35mm PC audio, VGA x2       Connectors - Outputs     3.5mm audio output, VGA       Audible Noise - Ece Mode     - 32 dBA at OF / -178°C       Audible Noise - Ece Mode     - 23 dBA at OF / -178°C       Audible Noise - Ece Mode     - 29 dBA at OF / -178°C       Included Accessories     Power corft, Remote, VGA cable, Documentation       30 Support     10800 gi 144 Hz via HDM, IDP Link 3D glases required       Product Warranty     9 of ays       Compatibility     6 months       Accessories Warranty     90 days       Compatibility     9.0 days       Conputer Compatibility     English, French, German, Spanish, Italian, Norwegian, Dutch, Smplified Chinese, Traditional Chinese, Korean, Smonish, Patish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Smonia	Color Wheel	6 segment, 2x speed
San Fraquery - Vertical24 KHzAspect Ratio43 GaldAspect Ratio Compatibility169, 1610Projection Distance - Maximum1mProjection Distance - Maximum1mProjection Distance - Maximum29 in CallInang Size - Maximum299 in CallProjection Offset15%Connectors - InputsHDM114. Composite video. Svideo. 35mm PC audio. VGA x2Connectors - Outputs3.5m audio output. VGAAudible Noise22 dBA at OF / 17B'CAudible Noise22 dBA at OF / 17B'CAudible Noise22 dBA at OF / 17B'CIncluded AccessoriesPower cord. Remote, VGA cable. Documentation10 Support1908 (B144 Hz via HDMI, DLP Link 3D glasses requiredProduct Warranty6 monthsComputer Compatibility90 daysComputer CompatibilityPC. MacOreal Computer CompatibilityPC. MacProtext VertauresKestop Context, French. German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Kerean, Smanish, Italian, Norwegian, Dutch, Simplified Chinese, Kerean, Smanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Kerean, Smanish, Italian, Norwegian, Dutch, Simplified Chinese, Creech, Seman, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Kerean, Smanish, Italian, Norwegian, Dutch, Simplified Chinese, Sterean, Smanish, Italian, Norwegian, Dutch, Simplified Chinese, Creech, Seman, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Smanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Smanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Smanish	Number of Colors	1.07 billion
Aspect Ratio43Aspect Ratio Canguability49Aspect Ratio Canguability10Projection Distance – Minimum1Projection Distance – Maximum20Image Size – Maximum29 inProjection Offset5%Connectors – InputsHDN1 14, Composite video, Svideo, S.5mn PC audo, VGA 24Connectors – Outputs35mn audio output, VGAAudible Noise – Eco Mode42 dBA at O'F / 178'CAudible Noise – Eco Mode42 dBA at O'F / 178'CAudible Noise – Eco Mode420 dBA at O'F / 178'CAudible Noise – Eco Mode90 erord, Remote, VGA cable, Documentation10kUgd AccessoriesPower cord, Remote, VGA cable, Documentation20 spopt108D g) 144 Hz via HDMI, DLP Link 3D glasses requiredProduct Warranty6 monthsAccessories Warranty0 dodysComputer Compatibility9 C, MacComputer Compatibility9 C, MacAmer LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Standard Lens –	Scan Frequency – Horizontal	15 KHz
Aspect Ratio43Aspect Ratio Canguability49Aspect Ratio Canguability10Projection Distance – Minimum1Projection Distance – Maximum20Image Size – Maximum29 inProjection Offset5%Connectors – InputsHDN1 14, Composite video, Svideo, S.5mn PC audo, VGA 24Connectors – Outputs35mn audio output, VGAAudible Noise – Eco Mode42 dBA at O'F / 178'CAudible Noise – Eco Mode42 dBA at O'F / 178'CAudible Noise – Eco Mode420 dBA at O'F / 178'CAudible Noise – Eco Mode90 erord, Remote, VGA cable, Documentation10kUgd AccessoriesPower cord, Remote, VGA cable, Documentation20 spopt108D g) 144 Hz via HDMI, DLP Link 3D glasses requiredProduct Warranty6 monthsAccessories Warranty0 dodysComputer Compatibility9 C, MacComputer Compatibility9 C, MacAmer LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Somish, Italian, Norwegian, Dutch, Simplified Chinese, Standard Lens –	Scan Frequency – Vertical	24 KHz
Aspect Ratio Compatibility169, 16:10Projection Distance – MinimumInProjection Distance – Minimum18Projection Distance – Minimum299 inImage Size – Maximum299 inProjection Offset15%Connetors – InputsHDM114, Composite video, S-video, 3.5mm PC audio, VGA x2Connetors – Outputs3.5mm audio output, VGAAudible Noise – Eco Mode<28 dBA at 0F / 17.8°C		4:3
Projection Distance - Maximum12 mLens TypeManual acom and focusImage Size - Maximum99 inProjection Offset15%Connectors - InputsHDMI 14, Composite video, Svideo, 35mm PC audio, VGA x2Connectors - Outputs35mm audio autput, VGAAudible Noise - Eco Mode- 29 dBA at 0°F / 178°CAudible Noise - Eco Mode- 29 dBA at 0°F / 178°CAudible Noise - Eco Mode- 29 dBA at 0°F / 178°CAudible Noise - Eco Mode- 90 wer cord, Remote, VGA cable, Documentation90 Support1080 e 014 Hz via HDMI, DLP Link 30 glasses requiredProduct Warranty60 mothsCacessories Warranty90 daysComputer Compatibility0 CAacComputer Compatibility10 to 0°T stressoriesAnnu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Smanian, HungarianSecurity FeaturesKensign Dinnish, Polish, Turkish, Danish, Prolish, Language, Uteta and Chinese, Korean, Smanian, HungarianSecurity FeaturesKensign Dinnish, Polish, Turkish, Danish, Parsian, Portuguese, Vietnamese, CzechThrow Ratio - Standard Lens - Minimum195Throw Ratio - Standard Len	Aspect Ratio Compatibility	16:9, 16:10
LenManual zoom and facusImage Size – Maximum299 inProjection Offset15%Connectors – InputsHDM 114, Composite video, S-video, 3.5mm PC audio, VGA x2Connectors – Outputs3.5mm audio output, VGAAudible Noise< 23 dBA at 0°F / -178°C	Projection Distance – Minimum	1 m
no299 inProjection Offset5%Connectors – InputsHDM1 14, Composite video, S.video, 3.5mm PC audio, VGA x2Connectors – Outputs3.5mm audio output, VGAAudible Noise< 32 dBA at 0°F / 17.8°C	Projection Distance – Maximum	12 m
Projection Offset     15%       Connectors - Inputs     HDM 14, Composite video, S.Simm PC audio, VGA x2       Connectors - Outputs     3.5mm audio output, VGA       Audible Noise     <23 dBA at 0°F / 178°C	Lens Type	Manual zoom and focus
Projection Offset     15%       Connectors - Inputs     HDM114, Composite video, S-video, 3.5mm PC audio, VGA x2       Connectors - Outputs     3.5mm audio output, VGA       Audible Noise     <23 dBA at 0°F / 17.8°C		299 in
Connectors – Inputs     HDMI 14. Composite video, S-video, 3.5mm PC audio, VGA x2       Connectors – Outputs     3.5mm audio output, VGA       Audible Noise     < 32 dBA at O'F / 17.8'C		15%
Connectors - Outputs3.5mm audio output, VGAAudible Noise< 32 dBA at O'F /-17.8'C		HDMI 1.4, Composite video, S-video, 3.5mm PC audio, VGA x2
Audible Noise     < 32 dBA at 0°F / 17.8°C		
Audible Noise – Eco Mode< 29 dBA at 0°F / 17.8°CIncluded AccessoriesPower cord, Remote, VGA cable, Documentation3D Support1080 p 0144 Hz via HDMI, DLP Link 3D glasses requiredProduct Warranty1 yearLamp Warranty6 monthsAccessories Warranty90 daysComputer CompatibilityPC, MacOperating Conditions11 to 104°F at 0 to 0 ft / 5 to 40°C at 0 to 0 mMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, HungarianSecurity FeaturesKensington lock portThrow Ratio – Standard Lens – Minimum1.95Throw Ratio – Standard Lens – Minimum1.95Throw Ratio – Standard Lens – Minimum3.5 x124 x 8.8 in / 8.8 y 315 x 223.5 mmProduct Weight5.2 lbs / 2.3 kgProduct Weight5.2 lbs / 2.3 kgShipping Dimensions8.8 x 33.4 t2 in / 1981 x 363.2 x 304.8 mm		
3D Support     1080p @ 144 Hz via HDMI, DLP Link 3D glasses required       Product Warranty     1 year       Lamp Warranty     6 months       Accessories Warranty     90 days       Computer Compatibility     9C, Mac       Operating Conditions     2 file 104°F at 0 to 0 ft / 5 to 40°C at 0 to 0 m       Security Features     Kensington lock port       Approvals     English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Atabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, Hungarian       Security Features     Kensington lock port       Approvals     UL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABO, CB, Nemco/GS, KC       Throw Ratio – Standard Lens – Minimum     1.95       Information – Standard Lens – Maximum     1.16       Spiping     Sis x 12.4 × 8.8 in / 88.9 x 315 x 22.35 mm       Product Weight     5.2 lbs / 2.3 kg       So 2 lbs / 2.3 kg     Sa x 14.3 x 12 in / 88.1 x 363.2 x 304.8 mm	Audible Noise – Eco Mode	< 29 dBA at 0°F / -17.8°C
Product WarrantyjvearLamp Warranty6 monthsAccessories Warranty90 daysComputer CompatibilityPC, MacOperating Conditions41 to 104'F at 0 to 0 ft / 5 to 40'C at 0 to 0 mMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, HungarianSecurity FeaturesKensington lock portApprovalsUL and c-UL, FCC, CC, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KCThrow Ratio – Standard Lens – Minimum1.95Throw Ratio – Standard Lens – Mainum2.15Zoom Ratio – Standard Lens – Mainum2.15Product DimensionsSas × 12.4 × 8.8 in / 8.8.9 × 315 × 22.3.5 mmProduct Weight5.2 los / 2.3 kgShipping Dimensions $38 \times 14.3 \times 12 in /188.1 × 363.2 × 30.4.8 mm$	Included Accessories	Power cord, Remote, VGA cable, Documentation
Product WarrantyjvearLamp Warranty6 monthsAccessories Warranty90 daysComputer CompatibilityPC, MacOperating Conditions41 to 104'F at 0 to 0 ft / 5 to 40'C at 0 to 0 mMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, HungarianSecurity FeaturesKensington lock portApprovalsUL and c-UL, FCC, CC, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KCThrow Ratio – Standard Lens – Minimum1.95Throw Ratio – Standard Lens – Mainum2.15Zoom Ratio – Standard Lens – Mainum2.15Product DimensionsSas × 12.4 × 8.8 in / 		
Lamp Warranty6 monthsAccessories Warranty90 daysComputer CompatibilityPC, MacOperating Conditions41 to 104"F at 0 to 0 ft / 5 to 40°C at 0 to 0 mMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, HungarianSecurity FeaturesKensington lock portApprovalUL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KCThrow Ratio – Standard Lens – Minimum1.95Throw Ratio – Standard Lens – Maximum2.15Zoom Ratio – Standard Lens – Maximum2.15Product Dimensions $\frac{35 \times 12.4 \times 8.8 in /}{8.89 \times 315 \times 22.35 mm}$ Product Weight5.2 los / 2.3 kgShipping Dimensions $\frac{78 \times 14.3 \times 12 in /}{198.1 \times 363.2 \times 304.8 mm}$		
Accessories Warranty90 daysComputer CompatibilityPC, MacOperating Conditions41 to 104"F at 0 to 0 ft / 5 to 40°C at 0 to 0 mMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, HungarianSecurity FeaturesKensington lock portApprovalsU Land c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KCThrow Ratio – Standard Lens – Minimum1.95Throw Ratio – Standard Lens – Maximum2.15Zoom Ratio – Standard Lens – Maximum3.5 × 12.4 × 8.8 in / 8.8 × 31.5 × 23.2 s mmProduct DimensionsSex 3.5 × 23.5 s mmProduct Weight5.2 los / 2.3 kgShipping Dimensions8.8 × 13.3 × 12 in / 98.1 × 363.2 × 304.8 mm		-
Computer CompatibilityPC, MacOperating Conditions41 to 104°F at 0 to 0 ft / 5 to 40°C at 0 to 0 mMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, HungarianSecurity FeaturesKensington lock portApprovalsUL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KCThrow Aratio – Standard Lens – Minimum1.95Throw Ratio – Standard Lens – Maximum2.15Zoom Ratio – Standard Lens – Maximum3.5 x 12.4 x 8.8 in / 88.9 x 315 x 223.5 mmProduct Dimensions3.5 x 12.4 x 8.8 in / 88.9 x 315 x 223.5 mmProduct Weight5.2 lbs / 2.3 kgShipping Dimensions8a x 14.3 x 12 in / 198.1 x 363.2 x 304.8 mm		
Operating Conditionslt to 104°F at 0 to 0 ff / sto 40°c at 0 to 0 mSupport at 0 to 0 ff / sto 40°c at 0 to 0 msto 40°c at 0 to 0 ff / sto 40°c at 0 to 0 mMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Komanian, HungarianSecurity FeaturesKensington lock portApprovalsU at 0 c-UL, FCC, CEC, CEC, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KCThrow Ratio - Standard Lens - Minimum1.95Arons Att - Standard Lens - Maximum1.95Som Ratio - Standard Lens - Maximum1.14Product DimensionsS5 x124 x 88 in / 89 x315 x 223.5 mmProduct Weight5.2 ls/2.3 kgShiping DimensionsSa x14.3 x12 in / 88.1 x 363.2 x 304.8 mm	Computer Compatibility	•
Menu LanguagesSwedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, HungarianSecurity FeaturesKensington lock portApprovalsUL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KCThrow Ratio – Standard Lens – Minimum1.95Throw Ratio – Standard Lens – Maximum2.15Zoom Ratio – Standard Lens1.11ShippingS5 × 12.4 × 8.8 in / 88.9 × 315 × 223.5 mmProduct Dimensions5.2 lbs / 2.3 kgShipping Dimensions7.8 × 14.3 × 12 in / 188.1 × 363.2 × 304.8 mm		
Approvals     UL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KC       Throw And Zoom     1       Throw Ratio – Standard Lens – Minimum     1.95       Throw Ratio – Standard Lens – Maximum     2.15       Zoom Ratio – Standard Lens – Maximum     1.11       Shipping     3.5 × 12.4 × 8.8 in / 88.9 × 315 × 223.5 mm       Product Dimensions     5.2 lbs / 2.3 kg       Shipping Dimensions     7.8 × 14.3 × 12 in / 198.1 × 363.2 × 304.8 mm	Menu Languages	Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech,
Throw and ZoomThrow Ratio – Standard Lens – Minimum1.95Throw Ratio – Standard Lens – Maximum2.15Zoom Ratio – Standard Lens1.1:1Shipping3.5 x 12.4 x 8.8 in / 88.9 x 315 x 223.5 mmProduct Dimensions3.5 x 12.4 x 8.8 in / 88.9 x 315 x 223.5 mmProduct Weight5.2 lbs / 2.3 kgShipping Dimensions7.8 x 14.3 x 12 in / 198.1 x 363.2 x 304.8 mm	Security Features	Kensington lock port
Throw Ratio – Standard Lens – Minimum   1.95     Throw Ratio – Standard Lens – Maximum   2.15     Zoom Ratio – Standard Lens   1.1:1     Shipping   3.5 × 12.4 × 8.8 in / 8.8 × 3.15 × 223.5 mm     Product Dimensions   5.2 lbs / 2.3 kg     Product Weight   5.2 lbs / 2.3 kg     Shipping Dimensions   7.8 × 14.3 × 12 in / 19.81 × 363.2 × 304.8 mm	Approvals	UL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KC
Throw Ratio – Standard Lens – Maximum   2.15     Zoom Ratio – Standard Lens   1.11     Shipping   3.5 x 12.4 x 8.8 in / 8.9 x 315 x 223.5 mm     Product Dimensions   3.5 x 12.4 x 8.8 in / 8.9 x 315 x 223.5 mm     Product Weight   5.2 lbs / 2.3 kg     Shipping Dimensions   7.8 x 14.3 x 12 in / 198.1 x 363.2 x 304.8 mm	Throw and Zoom	
Throw Ratio – Standard Lens – Maximum   2.15     Zoom Ratio – Standard Lens   11:1     Shipping   5.5 x 12.4 x 8.8 in / 8.9 x 315 x 22.3.5 mm     Product Dimensions   3.5 x 12.4 x 8.8 in / 8.9 x 315 x 22.3.5 mm     Product Weight   5.2 lbs / 2.3 kg     Shipping Dimensions   7.8 x 14.3 x 12 in / 19.8 x 303.2 x 304.8 mm	Throw Ratio – Standard Lens – Minimum	1.95
Zoom Ratio – Standard Lens     1.1.1       Shipping     3.5 × 12.4 × 8.8 in / 8.8 × 315 × 22.3.5 mm       Product Dimensions     3.5 × 12.4 × 8.8 in / 8.8 × 315 × 22.3.5 mm       Product Weight     5.2 lbs / 2.3 kg       Shipping Dimensions     7.8 × 14.3 × 12 in / 198.1 × 363.2 × 304.8 mm	Throw Ratio – Standard Lens – Maximum	
Shipping     3.5 x 12.4 x 8.8 in / 88.9 x 315 x 22.3 5 mm       Product Dimensions     3.5 x 12.4 x 8.8 in / 88.9 x 315 x 22.3 5 mm       Product Weight     5.2 lbs / 2.3 kg       Shipping Dimensions     7.8 x 14.3 x 12 in / 198.1 x 363.2 x 304.8 mm	Zoom Ratio – Standard Lens	
Product Dimensions     3.5 x 12.4 x 8.8 in / 88.9 x 315 x 223.5 mm       Product Weight     5.2 lbs / 2.3 kg       Shipping Dimensions     7.8 x 14.3 x 12 in / 198.1 x 363.2 x 304.8 mm	Shipping	
Product Weight     5.2 lbs / 2.3 kg       Shipping Dimensions     7.8 x 14.3 x 12 in / 198.1 x 363.2 x 304.8 mm		
Shipping Dimensions     7.8 x 14.3 x 12 in / 198.1 x 363.2 x 304.8 mm	Product Weight	
		7.8 x 14.3 x 12 in /
	Shipping Weight	7.3 lbs / 3.3 kg

\* Product specifications, terms, and offerings are subject to change at any time without notice.

#### Accessories

Universal Projector Ceiling Mount (PRJ-MNT-UNIV) Motorized Electric Projector Screen: 120 in., 4:3 (SC-MOT-120) Projector Lamp for the IN110v and IN220 Series (SP-LAMP-089) LiteShow 4 Wireless Adapter (INLITESHOW4) Presenter 4 RF Remote with Laser Pointer (HW-PRESENTER-4) Replacement Remote for Meeting Room Projectors (HW-NAVIGATOR-4) Presenter 3 RF Remote with Laser Pointer (HW-PRESENTER-3) Soft Carry Case for Office/Classroom Projector (CA-SOFTCASE-MTG) Soft Carry Case for Value Projectors (CA-SOFTVAL-2) Projector Ceiling Mount System (White) (PRJ-MNTKIT-UNIVW) Projector Ceiling Mount System (Black) (PRJ-MNTKIT-UNIVB) Projector Lock by PC Guardian (SEC-LOCK-01) Manual Pull Down Projector Screen: 84 in., 4:3 (SC-MAN-84) Manual Pull Down Projector Screen: 100 in., 4:3 (SC-MAN-100) Manual Pull Down Projector Screen: 120 in., 4:3 (SC-MAN-120) Motorized Electric Projector Screen: 84 in., 4:3 (SC-MOT-84) Motorized Electric Projector Screen: 100 in., 4:3 (SC-MOT-100) Fixed Frame Projector Screen: 84 in., 4:3 (SC-FF-84) Fixed Frame Projector Screen: 100 in., 4:3 (SC-FF-100) Fixed Frame Projector Screen: 120 in., 4:3 (SC-FF-120) Manual Pull Up Projector Screen: 80 in., 4:3 (SC-PU-80) Manual Pull Up Projector Screen: 100 in., 4:3 (SC-PU-100) 1 Year Extended Warranty for IN1XX Projectors (EPW-PJV1) 2 Year Extended Warranty for IN1XX Projectors (EPW-PJV2)