

Diamond 11 Specifications

Specifications	Diamond 11.0	Diamond 11.1	Diamond 11.2	Diamond 11.3
Configuration	2-way bookshelf	2-way bookshelf	2-way bookshelf	2.5-way floorstander
Enclosure type	Bass reflex (slot-loaded)	Bass reflex (slot-loaded)	Bass reflex (slot-loaded)	Bass reflex (slot-loaded)
Bass/mid driver	100mm woven Kevlar	130mm woven Kevlar	150mm woven Kevlar	130mm woven Kevlar
Bass driver	N/A	N/A	N/A	130mm woven Kevlar
Tweeter	25mm textile dome	25mm textile dome	25mm textile dome	25mm textile dome
Sensitivity	85dB	87dB	88dB	90dB
Recom'd amp power	15-75W	25-100W	25-125W	25-150W
Nominal impedance	8 Ohms compatible	8 Ohms compatible	8 Ohms compatible	8 Ohms compatible
Frequency response	75Hz-20kHz	55Hz-20kHz	48Hz-20kHz	44Hz-20kHz
Cabinet volume	3.95L	11.1L	13.2L	29.2L
Dimensions (HxWxD)	255x155x165mm	310x194x285mm	355x221x290mm	875x194x285mm
Weight (each)	3.1kg	6.8kg	9kg	15kg

Specifications	Diamond 11.4	Diamond 11.5	Diamond 11.CC	Diamond 11.CS
Configuration	3-way floorstander	3-way floorstander	2-way centre speaker	2-way centre speaker
Enclosure type	Bass reflex (slot-loaded)	Bass reflex (slot-loaded)	Bass reflex	Bass reflex
Bass/mid drivers	N/A	N/A	2x 100mm woven Kevlar	2x 130mm woven Kevlar
Bass drivers	2x 150mm woven Kevlar	2x 200mm woven Kevlar	N/A	N/A
Midrange driver	100mm woven Kevlar	100mm woven Kevlar	N/A	N/A
Tweeter	25mm textile dome	25mm textile dome	25mm textile dome	25mm textile dome
Sensitivity	91dB	90dB	87dB	87dB
Recom'd amp power	25-175W	25-200W	25-100W	25-150W
Nominal impedance	8 Ohms compatible	8 Ohms compatible	8 Ohms compatible	8 Ohms compatible
Frequency response	42Hz-20kHz	35Hz-20kHz	85Hz-20kHz	65Hz-20kHz
Cabinet volume	Mid 12L; Bass 30.9L	Mid 10.7; Bass 63L	5L	11L
Dimensions (HxWxD)	985x222x320mm	1125x290x350mm	145x420x138mm	170x480x200mm
Weight (each)	24kg	33.5kg	5kg	7.6kg