

Onkyo TX-L50

Download datasheet: [\[PDF\]](#)



Connections

Audio inputs- HDMI	5
AUX	Yes
AirPlay	Yes
Chromecast built in	Yes
FireConnect	Yes
Bluetooth	Yes
Bluetooth	Ja
Wifi	Yes
Wifi	Ja
LAN	Yes
LAN	Ja
Digital inputs coaxial	1

Digital inputs optical 1

Miscellaneous 1 x ARC

Cinch input stereo 3

Miscellaneous Input microphone

Bass driver output 1

High level speaker outputs 6

Headphone output 3,5mm 1

USB 2.0 Ja

Playback

Dolby Surround Yes

Dolby TrueHD Yes

DTS-HD High Resolution Audio Yes

DTS-HD Master Audio Yes

Dolby Digital Yes

DTS Yes

Dolby Digital Plus Yes

Dolby Pro Logic II Yes

Radio

Internet radio Yes

Station memory positions	40
RDS	Yes
FM - UKW	Yes
Miscellaneous	Integrated services: Spotify, Tunein, Deezer

Electronics

Automatic measuring	AccuEQ
Amplifier technology	Class-D
Amplifier configuration	5.1
Amplifier channels	6
Power output capacity sinus (RMS) Satellite	80 W
Power output capacity sinus (RMS) Bass	80 W
Power supply voltage	230 Volt volts
Standby-Function	Ja
Standby-Power consumption	0.38 watt
Maximum power consumption	60 watt
Mains lead fixed	Yes
Storage for settings when disconnected	Yes
Automatic on/off	Yes
High-Res Audio	Yes

Remote control Infrared

Power source AAA (2x)

Dimensions

Depth 32.50 cm

Width 43.50 cm

Height 7.00 cm

Weight 4 kg

Satellite Speaker CUB 2 FR 15 (pcs.)

High-end 2-way micro speakers with solid aluminium enclosures.



Speaker

Acoustic principle 2-Way-System

Enclosure type Bass reflex

Continuous power handling (IEC - Long Term) 100 Watt

Peak power capacity (IEC - Short Term) 140 Watt

Sensitivity (2.83 V / 1 m) 90 dB

Minimum amplifier output power recommended	20 Watt
Maximum sound pressure level	100 dB/1m
Impedance	4 - 8 Ohm
Frequency range from/to	200 - 20000 Hz
Crossover frequency internal switch	5000 Hz
Crossover frequency to Woofer (recommended)	150 - 200 Hz
Tweeter (number per enclosure)	1
Tweeter (diameter)	20.00 mm
Tweeter (material)	Seide
Midrange driver (number per enclosure)	2
Midrange driver (diameter)	80.00 mm
Midrange driver (material)	Cellulose, coated
Enclosure material	Aluminium
Enclosure surface	Anodised
Equalisation openings	2
Equalisation openings (pos.)	Back
Net internal volume	1.20 Litres
Wall mounting brackets	Yes
Keyhole plate mounted	Yes

Magnetic shielding Yes

Terminal clamps Gold-plated screw terminals

Suitable for banana plug Yes

Maximum cable diameter 4.00 mm

Suitable for AV receiver Yes

Connections

High level speaker outputs 1

Dimensions

Depth 9.70 cm

Width 18.80 cm

Height 9.50 cm

Weight 1.40 kg

Centre Speaker CUB 2 C 15

High-end 2-way micro loudspeaker made of solid aluminium



Speaker

Acoustic principle	2-Way-System
Enclosure type	Bass reflex
Continuous power handling (IEC - Long Term)	100 Watt
Peak power capacity (IEC - Short Term)	140 Watt
Sensitivity (2.83 V / 1 m)	90 dB
Minimum amplifier output power recommended	20 Watt
Maximum sound pressure level	100 dB/1m
Impedance	4 - 8 Ohm
Frequency range from/to	200 - 20000 Hz
Crossover frequency internal switch	5000 Hz
Crossover frequency to Woofer (recommended)	150 - 200 Hz
Tweeter (number per enclosure)	1
Tweeter (diameter)	20.00 mm
Tweeter (material)	Seide
Midrange driver (number per enclosure)	2
Midrange driver (diameter)	80.00 mm
Midrange driver (material)	Cellulose, coated
Enclosure material	Aluminium
Enclosure surface	Anodised

Equalisation openings 2

Equalisation openings (pos.) Back

Net internal volume 1.20 Litres

Wall mounting brackets Yes

Keyhole plate mounted Yes

Magnetic shielding Yes

Terminal clamps Gold-plated screw terminals

Suitable for banana plug Yes

Maximum cable diameter 4.00 mm

Suitable for AV receiver Yes

Connections

High Level loudspeaker inputs 1

Dimensions

Depth 9.70 cm

Width 9.50 cm

Height 18.80 cm

Weight 1.40 kg

T 8 Subwoofer

High-end active subwoofer, can be used either front- or down-firing



Speaker

Acoustic principle 1-Way-System

Downfire Yes

Frontfire Yes

Enclosure type Bass reflex

Maximum sound pressure level 111 dB/1m

Frequency range from/to 33-200 Hz Hz

Woofer (number per enclosure) 1

Woofer (diameter) 200.00 mm

Woofer (material) Aluminium

Enclosure type Bass reflex, DPU

Enclosure material MDF

Enclosure surface Matte coated

Equalisation openings 1

Integrated stand Yes

Miscellaneous	Reflection channel in DPU technology avoids flow noises, stable MDF housing structure with internal bracing
---------------	---

Suitable for AV receiver	Yes
--------------------------	-----

Connections

Cinch input	1
-------------	---

Miscellaneous	Suitable for installation directly on the wall
---------------	--

Electronics

Miscellaneous	Can be wirelessly controlled
---------------	------------------------------

Lowest frequency (-3 dB)	37 Hz
--------------------------	-------

Bass boost/EQ	Yes
---------------	-----

Input gain adjustment	Yes
-----------------------	-----

Frequency regulator (range)	37 - 200 Hz Hz
-----------------------------	----------------

Level control	Yes
---------------	-----

Phase control	Yes
---------------	-----

Miscellaneous	Can be used either front- or down-firing
---------------	--

Amplifier technology	Class-D
----------------------	---------

Amplifier configuration	1.0
-------------------------	-----

Amplifier channels	1
--------------------	---

Power output capacity impulse (peak) Bass	100 W
--	-------

Power supply voltage 230 Volt volts

Standby-Function Yes

Standby-Power consumption 1 watt

Maximum power consumption 100 watt

Mains lead fixed Yes

Safety class 2

Fuse Yes

Storage for settings when
disconnected Yes

Automatic on/off Yes

Dimensions

Depth 38.00 cm

Width 31.10 cm

Height 42.30 cm

Weight 11 kg
