

IN2124x

InFocus

Bright Network Projector with Flexible Connectivity

Part #: IN2124x

Leverage the high brightness, networking and optional wireless device casting of the InFocus IN2124x projector to increase the effectiveness, visibility and sharpness of your presentations and lessons.

Key Features

- ◆ XGA (1024 x 768) native resolution
- ◆ 4,200 lumens of brightness
- ◆ Network connectivity for easy management
- ◆ Display over HDMI or VGA
- ◆ PC-less display from USB drive or 4GB of internal memory
- ◆ 14,000:1 contrast ratio
- ◆ Powerful 10-watt speaker
- ◆ Assignable audio for connectivity options
- ◆ Blu-ray 3D capable (over HDMI)



Connection Flexibility

This feature-packed projector offers multiple connection options. Use HDMI and VGA inputs or the on-board file viewer to present photos, PowerPoint presentations, spreadsheets, PDFs, audio, video, and more; or present directly from a USB thumb drive. Make the IT team's job easier and connect the projector to your internal network for easy remote management, or sync it with your Crestron or AMX system.

LightCast Wireless Collaboration

Add a LightCast Key (not included) to easily connect and share content from your Apple, Windows, Android, or Chrome devices. Access the document viewer for PC-less presentation, and then browse the internet or use a digital whiteboard, all without connecting a device.*

* Wireless keyboard and mouse are recommended for digital whiteboard and internet browser usage.

High Brightness and Contrast

The image quality of the IN2124x will not disappoint. 4,200 lumens give you bright, clear images with the lights on and the high 14,000:1 contrast ratio adds sharpness with darker blacks and whiter whites.

Sound That Fills the Room

Big sound meets big images with a 10-watt speaker that ensure your audience doesn't miss a moment. Assign audio to mix and match sound with data and video sources, plus closed captioning capabilities ensure everyone can learn and understand more clearly.

Specifications*

Projector		IN2124x
Resolution – Native	XGA (1024 x 768)	
Resolution – Maximum	WUXGA (1920 x 1200)	
Display Technology	DLP	
Video Standard Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 720p, 1080i, 1080p	
Speakers	Mono 10W x 1	
Lamp Brightness	4,200 lumens	
Lamp Brightness – Low Power	3,360 lumens	
Lamp Life	2,000 hours	
Lamp Life – Low Power	5,000 hours	
Lamp Power	260W	
Lamp Power – Eco Mode	65W	
Replacement Lamp	SP-LAMP-094	
Contrast Ratio	14,000:1	
Color Wheel	6 segments, 2 vitesses	
Number of Colors	1.07 billion	
Aspect Ratio	4:3	
Aspect Ratio Compatibility	16:10	
Lens Type	Manual focus	
Projection Offset	15	
Keystone Correction	± 40°V	
Connectors – Inputs	3.5mm stereo audio x2, HDMI 1.4 (rear), Composite video, S-video, VGA x2	
Connectors – Outputs	3.5mm audio output, Monitor out (VGA)	
Audible Noise	< 34 dBA at 0°F / -17.8°C	
Audible Noise – Eco Mode	< 32 dBA at 0°F / -17.8°C	
Included Accessories	Power cord, Remote (no batteries), VGA cable, Documentation	
3D Support	720p @ 120Hz, 1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required	
Product Warranty	2 years	
Lamp Warranty	6 months	
Accessories Warranty	90 days	
PC-less Compatibility	USB 2.0 Type-A x2, File viewer/player, LightCast Key ready	
Video Player Compatibility	AVI, 3GP, MP4, MPEG-1 (MPG, MPEG), QuickTime (MOV, QT), RealMedia (RM, RMVB)	
Photo Viewer Compatibility	JPEG and JPG, PNG, Bitmap (BMP)	
Music Player Compatibility	MP3, WMA, AAC, WAV	
Operating Conditions	32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m	
Menu Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, Hungarian	
Security Features	User PIN, Security bar, Security lock slot	
Approvals	UL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KC	
Throw and Zoom		
Throw Ratio – Minimum	1.90:1	
Throw Ratio – Maximum	2.09:1	
Zoom Ratio	1.1:1	
Shipping		
Product Dimensions	3.9 x 11.5 x 8.7 in / 99.1 x 292.1 x 221 mm	
Product Weight	5.1 lbs / 2.3 kg	
Shipping Dimensions	7.8 x 14.3 x 12 in / 196.9 x 362 x 304.8 mm	
Shipping Weight	7.1 lbs / 3.2 kg	
UPC	797212982377	

* Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

Projector Lamp for the IN120x, IN120STx, and IN2120x Series (SP-LAMP-094)

LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)

InFocus Standard Replacement Remote (HW-NAVIGATOR-5)

LightCast Key (INA-LCKEY1)

LightCast Key (Europe) (INA-LCKEY2)

LightCast Key (Asia-Pacific) (INA-LCKEY3)

Presenter 4 RF Remote with Laser Pointer (HW-PRESENTER-4)

Replacement Remote for Meeting Room Projectors (HW-NAVIGATOR-4)

Soft Projector Carry Case (CA-SOFTCASE-MTG2)