



Dream team

Ultima 40 Surround "5.1-Set"

Discover pure audio enjoyment with this all-star line-up. You can only get this much surround sound for such a small budget from Teufel. Featuring our most popular floor-standing loudspeaker, the Ultima, of course.

Highlights:

- 5.1 top-of-the-range home cinema set with our bestselling Ultima 40 speakers
- High-quality home cinema, music and gaming sound with impressive surround sound and precise location of all sound events
- New: tweeter with phase plug, optimised sound dispersion, fine tuning across all components, more balanced sound, improved workmanship and design
- Powerful subwoofer, can be used either as a front- or down-firing subwoofer, optional wireless control
- 3-way system with two high-power woofers for high, distortion-free levels

Included components

- 1 x Centre speaker UL 40 C Mk3 18
- 2 x red rubber feet (4pcs.) for UL 20/40 Mk3 18
- 2 x UL 20 Mk3 18 bookshelf speaker (pc.)
- 2 x Floor speaker UL 40 Mk3 18 (pc.)
- 2 x red rubber feet (4pcs.) for UL 20/40 Mk3 18
- 1 x T 10 Subwoofer

Specifications

UL 20 Mk3 18 bookshelf speaker (pc.):

Speaker	Acoustic principle	2-Way-System
	Enclosure type	Bass reflex
	Continuous power handling (IEC - Long Term)	50 Watt
	Peak power capacity (IEC - Short Term)	80 Watt
	Sensitivity (2.83 V / 1 m)	87 dB
	Minimum amplifier output power recommended	20 Watt
	Maximum sound pressure level	104 dB/1m
	Impedance	4 Ohm
	Frequency range from/to	70 - 20.000 Hz
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	25.00 mm
	Tweeter (material)	Fabric weaving
	Bass/Midrange driver (number per enclosure)	1
	Bass/Midrange driver (diameter)	165.00 mm
	Bass/Midrange driver (material)	Fibreglass, chrome phase plug
	Enclosure material	MDF
	Enclosure surface	Laminated
	Equalisation openings	1
	Equalisation openings (pos.)	Rear side
	Removable front cover	Yes
	Net internal volume	10 Litres
	Wall mounting brackets	Yes
	Terminal clamps	Screw terminals, gold-plated
	Suitable for banana plug	Yes
	Maximum cable diameter	4.00 mm
	Crossover frequency internal switch	2600 Hz
Dimensions	Depth	23.50 cm
	Width	21.50 cm
	Height	33.50 cm

Weight	5.70 kg
Miscellaneous	Depth incl. grille. 25,0 cm

UL 40 C Mk3 18 centre speaker:

Speaker	Continuous power handling (IEC - Long Term)	100 Watt
	Peak power capacity (IEC - Short Term)	150 Watt
	Sensitivity (2.83 V / 1 m)	88 dB
	Maximum sound pressure level	107 dB/1m
	Impedance	4-8 Ohm
	Frequency range from/to	90 - 20.000 Hz
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	25.00 mm
	Tweeter (material)	Gewebe
	Bass/Midrange driver (number per enclosure)	2
	Bass/Midrange driver (diameter)	130.00 mm
	Bass/Midrange driver (material)	Kevlar/Fiberglas mit verchromten Phase Plug
	Terminal clamps	Schraubklemmen, vergoldet
	Suitable for banana plug	Yes
	Maximum cable diameter	4.00 mm
Dimensions	Depth	15.90 cm
	Width	42.00 cm
	Height	16.90 cm
	Weight	5.70 kg
	Miscellaneous	Tiefe mit Schutzgitter: 17,1 cm Tiefe mit Schutzgitter und Wandhalter: 18,5 cm

UL 40 Mk3 18 tower speaker (pcs.):

Speaker	Acoustic principle	3-Way-System
	Enclosure type	Bass reflex
	Continuous power handling (IEC - Long Term)	120 Watt
	Peak power capacity (IEC - Short Term)	200 Watt
	Sensitivity (2.83 V / 1 m)	87 dB
	Maximum sound pressure level	108 dB/1m
	Impedance	4-8 Ohm
	Frequency range from/to	45 - 20,000 Hz
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	25.00 mm
	Tweeter (material)	Fabric weaving
	Midrange driver (number per enclosure)	1
	Midrange driver (diameter)	165.00 mm

	Midrange driver (material)	Kevlar, chrome phase plug
	Woofer (number per enclosure)	2
	Woofer (diameter)	165.00 mm
	Woofer (material)	Fibreglass
	Miscellaneous	Hochtöner mit Phase Plug, Material: Stahl
	Enclosure material	MDF
	Enclosure surface	Laminated
	Equalisation openings	2
	Equalisation openings (pos.)	Rear side
	Removable front cover	Yes
	Net internal volume	54 Litres
	Spikes prepared	Yes
	Integrated stand	Yes
	Terminal clamps	Screw terminal, gold-plated
	Suitable for banana plug	Yes
	Bi-Amping/Bi-Wiring	Yes
	Maximum cable diameter	4.00 mm
	Suitable for AV receiver	Yes
Dimensions	Depth	32.00 cm
	Width	21.50 cm
	Height	106.50 cm
	Weight	20 kg
	Miscellaneous	Base plate dimensions: depth: 35 cm / width: 25 cm

T 10 Subwoofer:

Speaker	Acoustic principle	1-Way-System
	Downfire	Yes
	Frontfire	Yes
	Enclosure type	Bass reflex
	Maximum sound pressure level	115 dB/1m
	Frequency range from/to	37 - 200 Hz Hz
	Woofer (number per enclosure)	1
	Woofer (diameter)	250.00 mm
	Woofer (material)	Aluminium
	Enclosure material	MDF
	Enclosure surface	Matte coated
	Equalisation openings	1
	Integrated stand	Yes
	Miscellaneous	Reflection channel in DPU technology avoids flow noises, stable MDF housing structure

		with internal bracing
Connections	Suitable for AV receiver	Yes
	Cinch input	1
Electronics	Lowest frequency (-3 dB)	33 Hz
	Bass boost/EQ	Yes
	Input gain adjustment	Yes
	Level control	Yes
	Phase control	Yes
	Miscellaneous	Can be used either front- or down-firing
	Amplifier technology	Class-D
	Amplifier configuration	1.0
	Amplifier channels	1
	Power output capacity impulse (peak) Bass	150 W
	Power supply voltage	230 Volt volts
	Standby-Function	Yes
	Standby-Power consumption	1 watt
	Maximum power consumption	150 watt
	Mains lead fixed	Yes
	Safety class	2
	Fuse	Yes
	Storage for settings when disconnected	Yes
	Automatic on/off	Yes
	Miscellaneous	Wireless subwoofer module integrated (subwoofer with compatible feeders can be controlled wirelessly)
Dimensions	Depth	38.00 cm
	Width	35.10 cm
	Height	48.30 cm
	Weight	15.60 kg