

Home Cinema Projector

# Vivitek H1060

Affordable FullHD 3D ready home cinema projector with high contrast, long life lamp, dual HDMI inputs and built-in speaker



## Features

- Full high definition 1080p (1920x1080) resolution scalable up to a maximum WUXGA (1920x1200)
- Bright 3,000 ANSI lumens and a high 15,000:1 contrast ratio ensuring a crisp and sharp image
- DLP® technology with BrilliantColor™ for a vibrant and rich picture quality
- Six segment GYRWCBC color wheel for outstanding color reproduction
- 8 pre-set display modes to get the most suitable display image
- Multiple inputs for easy connection to a variety of devices: HDMI, MHL/HDMI, VGA-In, Audio-In/Out, 3D-Sync Out, Mini-USB (Service)
- MHL device compatibility for video and audio content streaming from a compatible mobile device
- 3D ready with DLP® Link™ and Blu-ray 3D technologies
- 3D sync port for compatibility with IR (infrared) 3D passive synchronization protocol
- Audio ready with built-in 2 watt audio speaker, audio-in and audio out ports
- Energy efficient lamps that last up to 10,000 hours (Dynamic Eco. Mode)
- Conveniently adjust the zoom and focus manually at the turn of a button
- Top sided lamp cover for simple lamp removal and insertion
- Source filtering function to save time locating device signal source
- Integrated Closed Caption Decoding (CCD) automatically converts a TV's audio signal in subtitles
- Convenient top loading design for easy lamp replacement
- Keypad lock prevents accidental system adjustments
- 2.3kg/5lbs for easy portability

## Specifications

Display Type	Single 0.65" DLP® Technology by TI
Brightness	3,000 ANSI Lumens
Native Resolution	1080p (1920 x 1080p)
Maximum Resolution	WUXGA (1920x1200)@60Hz
Contrast Ratio	15,000:1
Lamp Life/Type	5,000/6,000/10,000 Hours (Normal/Eco. Mode/Dynamic Eco. Mode), 190W/160W
Throw Ratio	1.14 - 1.5:1
Image Size (Diagonal)	30.1" - 317"
Projection Distance	1m - 8m (3.287ft - 26.24ft)
Projection Lens	f = 2.59 - 2.91, f=16.87 - 21.87mm
Zoom Ratio	1.3x
Aspect Ratio	16:9 Native
Offset	115% ±10%
Keystone Correction	Vertical +/-40°
Horizontal Frequency	15, 31 – 91.4kHz
Vertical Frequency	24 - 30Hz, 47 - 120Hz
3D Functionality	Yes (Via DLP® Link™, Blu-ray 3D)
Speakers	2W (Mono)
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
I/O Connection Ports	HDMI v1.4, MHL/HDMI v1.4, VGA-In, Audio-In (Mini-Jack), Audio-Out (Mini-Jack), 3D-Sync Out, 12v Trigger (Mini-Jack), Mini-USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Keypad Lock (Power Only)
Dimensions (W x D x H)	274.6 x 212 x 100mm (10.8" x 8.3" x 3.9")
Weight	2.3kg (5lbs)
Available Color	Two-Tone: White/Gray
Noise Level	34dB/31dB (Normal/Eco Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	200 (Eco. Mode), 240W (Normal Mode), <0.5W (Standby)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Documentation Kit
Optional Accessories	Replacement Lamp, Filter, Lens Cap, Carry Case

©2015 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

## Photos

