



Teamwork

Cubycon Impaq Streaming

Cubycon Impaq Streaming offers everything avid home cinema owners need, without dominating the entire living room. Small set, large sound, with a Blu-ray receiver and Spotify network player. The system is immediately ready to play and perfectly configured.

Highlights:

- Complete 5.1 Blu-ray system with 4K UHD support and the best sound in its class
- Buy as a bundle and save: Contains Blu-ray receiver, loudspeakers & network audio player for music streaming
- MKV and DivX-HD support, FM radio with RDS, USB, 7.1 option, slot-loading drive, NFC, aptX, LAN
- Integrated slimline Blu-ray AV receiver with HD audio, 3D, Bluetooth streaming and DLNA
- Perfectly proportioned components, plug-&-play, comes with high-end cable set

Included components

- 4 x Satellite Speaker CUB 2 FR 15 (pcs.)
- 1 x Centre Speaker CUB 2 C 15
- 1 x Impaq 8000 Blu-ray Receiver
- 1 x power cable
- 1 x FM antenna for IP 8000 BR
- 1 x IP 8000 RC Remote Control
- 1 x Subwoofer T 4000 SW (without wireless module)
- 1 x Teufel Connector
- 1 x Ethernet cable 2m
- 1 x power adapter
- 1 x HDMI-Cable 1.4 1.5m - C1515V
- 1 x 30m Speaker Cable 1.0mm² - C1030S
- 1 x SubConnect MOD

Specifications

Impaq 8000 Blu-ray Receiver:

| | | |
|--------------------|----------------------------|----------|
| Connections | 4K UHD Upscale | Yes |
| | Bluetooth | Yes |
| | Bluetooth | Yes |
| | Wifi | Yes |
| | Wifi | Optional |
| | LAN | Yes |
| | LAN | 1 |
| | NFC | Yes |
| | Digital inputs coaxial | 1 |
| | Digital inputs optical | 1 |
| | Cinch input stereo | 1 |
| | Cinch output stereo | 1 |
| | Bass driver output | 1 |
| | High level speaker outputs | 5 |
| | Video inputs- HDMI | 3 |
| | Video inputs- HDMI | Yes |
| | HDMI Version | 1.4b |
| | Miscellaneous | HDMI 3D |
| | Video outputs - HDMI | 1 |
| | Video outputs - HDMI | Yes |
| | HDMI Version | 1.4b |
| | USB 2.0 | 2 |
| Playback | ASF | Yes |
| | Dolby TrueHD | Yes |

| | |
|---------------------|-----|
| DTS-HD Master Audio | Yes |
| Dolby Digital | Yes |
| DTS | Yes |
| MP2 | Yes |
| MP3 | Yes |
| WMA | Yes |
| WAV | Yes |
| AAC | Yes |
| FLAC | Yes |
| OGG | Yes |
| HDCD | Yes |
| M4A | Yes |
| Apple Lossless | Yes |
| Dolby Digital Plus | Yes |
| Dolby Pro Logic | Yes |
| Dolby Pro Logic II | Yes |
| Dolby Headphone | Yes |
| JPEG | Yes |
| GIF | Yes |
| BMP | Yes |
| FLV | Yes |
| MPEG1 | Yes |
| MPEG2 | Yes |
| MPEG4 | Yes |
| DivX | Yes |
| DivX HD | Yes |
| RealMedia | Yes |
| Xvid | Yes |
| AVC/H.264 | Yes |
| WMV | Yes |
| MKV | Yes |
| CD-Audio | Yes |
| VCD | Yes |
| SVCD | Yes |
| DVD-Video | Yes |
| DVD-Audio | Yes |
| Blu-ray | Yes |
| BDMV | Yes |
| BDAV | Yes |
| CD | Yes |
| DVD | Yes |

| | | |
|--------------------|--|-------------------|
| | Blu-ray | Yes |
| | CD-R | Yes |
| | CD-RW | Yes |
| | DVD-R | Yes |
| | DVD+R | Yes |
| | DVD-RW | Yes |
| | DVD+RW | Yes |
| | DVD-RAM | Yes |
| | BD-R | Yes |
| | BD-RE | Yes |
| Radio | Radio present | Yes |
| | Channel memory slot - FM | 30 |
| | RDS | Yes |
| | FM - UKW | Yes |
| Electronics | 10-Mbit/s Ethernet | Yes |
| | 10/100-Mbit/s Ethernet | Yes |
| | Miscellaneous | DLNA |
| | Amplifier technology | Class-D |
| | Amplifier configuration | 5.0 |
| | Amplifier channels | 5 |
| | Power output capacity impulse (peak) Satellite | 100 W |
| | Power output capacity sinus (RMS) Satellite | 75 W |
| | Power supply voltage | 230 Volt volts |
| | Standby-Function | Yes |
| | Standby-Power consumption | 0.40 watt |
| | Maximum power consumption | 700 watt |
| | Mains cable - IEC connector (non-heating device) | Yes |
| | Safety class | 2 |
| | Storage for settings when disconnected | Yes |
| | Automatic on/off | Yes |
| | Display | Yes |
| | OSD | Yes |
| | Integrated DSP | Yes |
| | Audio-Digital-Analog-Converter | Texas Instruments |
| | Integrated DD/dts/PLII-Decoder | Yes |
| | Integrated True HD/dts HD/DD/dts/PLII-Decoder | Yes |
| | Remote control | Infrared |
| | Power source | AAA |
| Dimensions | Depth | 36.00 cm |
| | Width | 40.00 cm |
| | Height | 8.00 cm |

| | |
|--------|---------|
| Weight | 4.80 kg |
|--------|---------|

Satellite Speaker CUB 2 FR 15 (pcs.):

| | | |
|--------------------|---|-----------------------------|
| Speaker | Acoustic principle | 2-Way-System |
| | Enclosure type | Bass reflex |
| | Continuous power handling (IEC - Long Term) | 100 Watt |
| | Peak power capacity (IEC - Short Term) | 140 Watt |
| | Sensitivity (2.83 V / 1 m) | 90 dB |
| | Minimum amplifier output power recommended | 20 Watt |
| | Maximum sound pressure level | 100 dB/1m |
| | Impedance | 4 - 8 Ohm |
| | Frequency range from/to | 200 - 20000 Hz |
| | Crossover frequency internal switch | 5000 Hz |
| | Crossover frequency to Woofer (recommended) | 150 - 200 Hz |
| | Tweeter (number per enclosure) | 1 |
| | Tweeter (diameter) | 20.00 mm |
| | Tweeter (material) | Seide |
| | Midrange driver (number per enclosure) | 2 |
| | Midrange driver (diameter) | 80.00 mm |
| | Midrange driver (material) | Cellulose, coated |
| | Enclosure material | Aluminium |
| | Enclosure surface | Anodised |
| | Equalisation openings | 2 |
| | Equalisation openings (pos.) | Back |
| | Net internal volume | 1.20 Litres |
| | Wall mounting brackets | Yes |
| | Keyhole plate mounted | Yes |
| | Magnetic shielding | Yes |
| | Terminal clamps | Gold-plated screw terminals |
| | Suitable for banana plug | Yes |
| | Maximum cable diameter | 4.00 mm |
| | Suitable for AV receiver | Yes |
| Connections | High level speaker outputs | 1 |
| Dimensions | Depth | 9.70 cm |
| | Width | 18.80 cm |
| | Height | 9.50 cm |
| | Weight | 1.40 kg |

Subwoofer T 4000:

| | | |
|----------------|--------------------|--------------|
| Speaker | Acoustic principle | 1-Way-System |
| | Downfire | Yes |
| | Enclosure type | Bass reflex |

| | | |
|--------------------|--|---------------------------|
| | Maximum sound pressure level | 102 dB/1m |
| | Frequency range from/to | 35-200 Hz Hz |
| | Woofer (number per enclosure) | 3 |
| | Woofer (diameter) | 130.00 mm |
| | Woofer (material) | Cellulose, coated |
| | Miscellaneous | Extreme stroke capability |
| | Enclosure material | MDF |
| | Enclosure surface | Matte lacquer |
| | Integrated stand | Yes |
| | Suitable for AV receiver | Yes |
| Connections | Cinch input stereo | 1 |
| Electronics | Lowest frequency (-3 dB) | 35 Hz |
| | Input gain adjustment | Yes |
| | Frequency regulator (range) | Yes Hz |
| | Phase control | Yes |
| | Amplifier technology | Class-D |
| | Amplifier configuration | 1.0 |
| | Amplifier channels | 1 |
| | Power output capacity impulse (peak) Bass | 240 W |
| | Power output capacity sinus (RMS) Bass | 150 W |
| | Miscellaneous | DSP from analogue devices |
| | Power supply voltage | 230 Volt volts |
| | Standby-Function | Yes |
| | Standby-Power consumption | 0.40 watt |
| | Mains cable - IEC connector (non-heating device) | Yes |
| | Safety class | 2 |
| | Fuse | Yes |
| | Storage for settings when disconnected | Yes |
| | Automatic on/off | Yes |
| Dimensions | Depth | 30.00 cm |
| | Width | 95.50 cm |
| | Height | 12.50 cm |
| | Weight | 13.20 kg |

Centre Speaker CUB 2 C 15:

| | | |
|----------------|---|--------------|
| Speaker | Acoustic principle | 2-Way-System |
| | Enclosure type | Bass reflex |
| | Continuous power handling (IEC - Long Term) | 100 Watt |
| | Peak power capacity (IEC - Short Term) | 140 Watt |
| | Sensitivity (2.83 V / 1 m) | 90 dB |
| | Minimum amplifier output power recommended | 20 Watt |
| | Maximum sound pressure level | 100 dB/1m |

| | | |
|--------------------|---|-----------------------------|
| | Impedance | 4 - 8 Ohm |
| | Frequency range from/to | 200 - 20000 Hz |
| | Crossover frequency internal switch | 5000 Hz |
| | Crossover frequency to Woofer (recommended) | 150 - 200 Hz |
| | Tweeter (number per enclosure) | 1 |
| | Tweeter (diameter) | 20.00 mm |
| | Tweeter (material) | Seide |
| | Midrange driver (number per enclosure) | 2 |
| | Midrange driver (diameter) | 80.00 mm |
| | Midrange driver (material) | Cellulose, coated |
| | Enclosure material | Aluminium |
| | Enclosure surface | Anodised |
| | Equalisation openings | 2 |
| | Equalisation openings (pos.) | Back |
| | Net internal volume | 1.20 Litres |
| | Wall mounting brackets | Yes |
| | Keyhole plate mounted | Yes |
| | Magnetic shielding | Yes |
| | Terminal clamps | Gold-plated screw terminals |
| | Suitable for banana plug | Yes |
| | Maximum cable diameter | 4.00 mm |
| | Suitable for AV receiver | Yes |
| Connections | High Level loudspeaker inputs | 1 |
| Dimensions | Depth | 9.70 cm |
| | Width | 9.50 cm |
| | Height | 18.80 cm |
| | Weight | 1.40 kg |

Teufel Connector:

| | | |
|--------------------|-------------------------|-----|
| Connections | Wifi | Yes |
| | Wifi | 1 |
| | LAN | Yes |
| | LAN | 1 |
| | Digital outputs optical | 1 |
| | Cinch input stereo | 1 |
| | Cinch output stereo | 1 |
| | USB 2.0 | 1 |
| Playback | MP3 | Yes |
| | WMA | Yes |
| | WAV | Yes |
| | AAC | Yes |
| | FLAC | Yes |

| | | |
|------------------------|-------------------------|---------------------------|
| | OGG | Yes |
| | Apple Lossless | Yes |
| | Miscellaneous | Supports gapless playback |
| Radio | Internet radio | Yes |
| | Sleeptimer | Yes |
| Electronics | Maximum number of items | 150.000 |
| | Infrastructure mode | Yes |
| | WLAN Standards | 802.11b/g/n |
| | WLAN encryption | WPA, WPA2 |
| | 10/100-Mbit/s Ethernet | Yes |
| | Multi-room | Yes |
| | Power supply voltage | 230 Volt volts |
| | Standby-Function | Yes |
| | Automatic on/off | Yes |
| Dimensions | Depth | 12.70 cm |
| | Width | 17.20 cm |
| | Height | 2.80 cm |
| | Weight | 0.29 kg |
| SubConnect MOD: | | |
| Dimensions | Depth | 9.00 cm |
| | Width | 6.40 cm |
| | Height | 2.40 cm |
| | Weight | 0.08 kg |