



Mini but mighty

Cubycon Complete

The new Cubycon Complete is Teufel's premium compact high-end system. Enjoy the convenience of single purchase plug-&-play home cinema, now with improved satellites for even better sound quality. The subwoofer and A/V receiver are nearly invisible for maximum sound with minimal living room disruption.

Highlights:

- Plug-&-play 5.1 complete system with flat subwoofer & A/V receiver
- Balanced, neutral, detailed playback with music, movies and games
- 3 bass drivers in the subwoofer generate deep, dry bass down to 35 Hz
- The CoreStation is an ultra-compact A/V receiver for inconspicuous operation
- Bluetooth 4.0, HDMI, 3D support, 360 watt class D amplifier from Texas Instruments

Included components

- 4 x Satellite Speaker CUB 2 FR 15 (pcs.)
- 1 x Centre Speaker CUB 2 C 15
- 1 x Subwoofer T 4000 SW (without wireless module)
- 1 x CoreStation
- 1 x power cable
- 1 x Remote Control for Corestation
- 1 x 30m Speaker Cable 1.0mm² - C1030S
- 1 x HDMI-Cable 1.4 1.5m - C1515V
- 1 x SubConnect MOD

Specifications

CoreStation:

Connections	Bluetooth aptX	Yes
	Bluetooth	Yes
	Bluetooth	4.0 with aptX
	Digital inputs coaxial	1
	Digital inputs optical	2
	Cinch input	1
	Stereo jack 3.5mm - in	2
	High level speaker outputs	5
	Headphone output 3,5mm	1
	Video inputs- HDMI	4
	HDMI Version	1.4a (3D)
	Video outputs - HDMI	1
	Video outputs - HDMI	Yes
	HDMI Version	1.4a (3D)
	Miscellaneous	USB port for software updates
Playback	Dolby Digital	Yes
	DTS	Yes
	Dolby Pro Logic II	Yes
	Dolby Pro Logic II	Music, movies
Radio	Radio present	Yes
	Channel memory slot - FM	30
	FM - UKW	Yes
Electronics	Amplifier technology	Class-D
	Amplifier configuration	5.0
	Amplifier channels	5
	Power output capacity impulse (peak) Satellite	100 W
	Power output capacity sinus (RMS) Satellite	80 W

	Performance measured by (Ohm)	4
	Miscellaneous	30 Watt/Rear
	Power supply voltage	230 Volt volts
	Standby-Function	Yes
	Standby-Power consumption	0.40 watt
	Maximum power consumption	500 watt
	Mains cable - IEC connector (non-heating device)	Yes
	Safety class	2
	Storage for settings when disconnected	Yes
	Miscellaneous	Automatic off
	Integrated DSP	Yes
	Integrated DD/dts/PLII-Decoder	Yes
	Remote control	Radio
	Materials	Aluminium
	Presets	Yes
Dimensions	Depth	24.00 cm
	Width	30.80 cm
	Height	6.30 cm
	Weight	3.40 kg

Satellite Speaker CUB 2 FR 15 (pcs.):

Speaker	Acoustic principle	2-Way-System
	Enclosure type	Bass reflex
	Continuous power handling (IEC - Long Term)	100 Watt
	Peak power capacity (IEC - Short Term)	140 Watt
	Sensitivity (2.83 V / 1 m)	90 dB
	Minimum amplifier output power recommended	20 Watt
	Maximum sound pressure level	100 dB/1m
	Impedance	4 - 8 Ohm
	Frequency range from/to	200 - 20000 Hz
	Crossover frequency internal switch	5000 Hz
	Crossover frequency to Woofer (recommended)	150 - 200 Hz
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	20.00 mm
	Tweeter (material)	Seide
	Midrange driver (number per enclosure)	2
	Midrange driver (diameter)	80.00 mm
	Midrange driver (material)	Cellulose, coated
	Enclosure material	Aluminium
	Enclosure surface	Anodised
	Equalisation openings	2

	Equalisation openings (pos.)	Back
	Net internal volume	1.20 Litres
	Wall mounting brackets	Yes
	Keyhole plate mounted	Yes
	Magnetic shielding	Yes
	Terminal clamps	Gold-plated screw terminals
	Suitable for banana plug	Yes
	Maximum cable diameter	4.00 mm
	Suitable for AV receiver	Yes
Connections	High level speaker outputs	1
Dimensions	Depth	9.70 cm
	Width	18.80 cm
	Height	9.50 cm
	Weight	1.40 kg

Subwoofer T 4000:

Speaker	Acoustic principle	1-Way-System
	Downfire	Yes
	Enclosure type	Bass reflex
	Maximum sound pressure level	102 dB/1m
	Frequency range from/to	35-200 Hz Hz
	Woofer (number per enclosure)	3
	Woofer (diameter)	130.00 mm
	Woofer (material)	Cellulose, coated
	Miscellaneous	Extreme stroke capability
	Enclosure material	MDF
	Enclosure surface	Matte lacquer
	Integrated stand	Yes
	Suitable for AV receiver	Yes
Connections	Cinch input stereo	1
Electronics	Lowest frequency (-3 dB)	35 Hz
	Input gain adjustment	Yes
	Frequency regulator (range)	Yes Hz
	Phase control	Yes
	Amplifier technology	Class-D
	Amplifier configuration	1.0
	Amplifier channels	1
	Power output capacity impulse (peak) Bass	240 W
	Power output capacity sinus (RMS) Bass	150 W
	Miscellaneous	DSP from analogue devices
	Power supply voltage	230 Volt volts
	Standby-Function	Yes

	Standby-Power consumption	0.40 watt
	Mains cable - IEC connector (non-heating device)	Yes
	Safety class	2
	Fuse	Yes
	Storage for settings when disconnected	Yes
	Automatic on/off	Yes
Dimensions	Depth	30.00 cm
	Width	95.50 cm
	Height	12.50 cm
	Weight	13.20 kg

Centre Speaker CUB 2 C 15:

Speaker	Acoustic principle	2-Way-System
	Enclosure type	Bass reflex
	Continuous power handling (IEC - Long Term)	100 Watt
	Peak power capacity (IEC - Short Term)	140 Watt
	Sensitivity (2.83 V / 1 m)	90 dB
	Minimum amplifier output power recommended	20 Watt
	Maximum sound pressure level	100 dB/1m
	Impedance	4 - 8 Ohm
	Frequency range from/to	200 - 20000 Hz
	Crossover frequency internal switch	5000 Hz
	Crossover frequency to Woofer (recommended)	150 - 200 Hz
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	20.00 mm
	Tweeter (material)	Seide
	Midrange driver (number per enclosure)	2
	Midrange driver (diameter)	80.00 mm
	Midrange driver (material)	Cellulose, coated
	Enclosure material	Aluminium
	Enclosure surface	Anodised
	Equalisation openings	2
	Equalisation openings (pos.)	Back
	Net internal volume	1.20 Litres
	Wall mounting brackets	Yes
	Keyhole plate mounted	Yes
	Magnetic shielding	Yes
	Terminal clamps	Gold-plated screw terminals
	Suitable for banana plug	Yes
	Maximum cable diameter	4.00 mm
	Suitable for AV receiver	Yes
	Connections	High Level loudspeaker inputs
		1

Dimensions	Depth	9.70 cm
	Width	9.50 cm
	Height	18.80 cm
	Weight	1.40 kg

SubConnect MOD:

Dimensions	Depth	9.00 cm
	Width	6.40 cm
	Height	2.40 cm
	Weight	0.08 kg