

Onkyo TX-L50

Download datasheet: [\[PDF\]](#)



Connections

Audio inputs- HDMI	5
AUX	Yes
AirPlay	Yes
Chromecast built in	Yes
FireConnect	Yes
Bluetooth	Yes
Bluetooth	Ja
Wifi	Yes
Wifi	Ja
LAN	Yes
LAN	Ja
Digital inputs coaxial	1

Digital inputs optical	1
Miscellaneous	1 x ARC
Cinch input stereo	3
Miscellaneous	Input microphone
Bass driver output	1
High level speaker outputs	6
Headphone output 3,5mm	1
USB 2.0	Ja

Playback

Dolby Surround	Yes
Dolby TrueHD	Yes
DTS-HD High Resolution Audio	Yes
DTS-HD Master Audio	Yes
Dolby Digital	Yes
DTS	Yes
Dolby Digital Plus	Yes
Dolby Pro Logic II	Yes

Radio

Internet radio	Yes
----------------	-----

Station memory positions	40
RDS	Yes
FM - UKW	Yes
Miscellaneous	Integrated services: Spotify, Tunein, Deezer

Electronics

Automatic measuring	AccuEQ
Amplifier technology	Class-D
Amplifier configuration	5.1
Amplifier channels	6
Power output capacity sinus (RMS) Satellite	80 W
Power output capacity sinus (RMS) Bass	80 W
Power supply voltage	230 Volt volts
Standby-Function	Ja
Standby-Power consumption	0.38 watt
Maximum power consumption	60 watt
Mains lead fixed	Yes
Storage for settings when disconnected	Yes
Automatic on/off	Yes
High-Res Audio	Yes

Remote control Infrared

Power source AAA (2x)

Dimensions

Depth 32.50 cm

Width 43.50 cm

Height 7.00 cm

Weight 4 kg

Satellite-Speaker CS 35 FCR Mk3

A 2-way satellite speaker with a powerful 80 mm midrange driver and a high fidelity 19 mm tweeter. A high load capacity ensures loud volumes with low levels of distortion. Balanced, universal tuning makes this speaker equally suitable for film, music, and gaming sound. Robust metal grilles on the enclosure protect the drivers.

The CS 35 FCR Mk3 cannot be purchased separately.

Show more information



Speaker

Acoustic principle 2-Way-System

Enclosure type Closed

Continuous power handling (IEC - Long Term)	80 Watt
Peak power capacity (IEC - Short Term)	160 Watt
Sensitivity (2.83 V / 1 m)	88 dB
Minimum amplifier output power recommended	10 Watt
Maximum sound pressure level	105 dB/1m
Impedance	4 - 8 Ohm
Frequency range from/to	150 - 20000 Hz
Crossover frequency internal switch	3400 Hz
Crossover frequency to Woofer (recommended)	150 - 180 Hz
Miscellaneous	Neutral tuning
Tweeter (number per enclosure)	1
Tweeter (diameter)	19.00 mm
Tweeter (material)	Silk
Midrange driver (number per enclosure)	2
Midrange driver (diameter)	80.00 mm
Midrange driver (material)	Cellulose, coated
Miscellaneous	High excursion drivers
Enclosure material	Synthetic
Enclosure surface	Impact-resistant lacquer, matte

Net internal volume 1.20 Litres

Diameter of the stand screw threads 6.00 mm

Keyhole plate mounted Yes

Miscellaneous Strong walls minimize resonances

Maximum cable diameter 2.50 mm

Suitable for AV receiver Yes

Miscellaneous requires little power for high levels

Dimensions

Depth 9.50 cm

Width 10.00 cm

Height 22.60 cm

Weight 1.25 kg

Centre Speaker CS 35 C Mk3

A 2-way satellite speaker with a powerful 80 mm midrange driver and a high fidelity 19 mm tweeter.



Speaker

Acoustic principle	2-Way-System
Enclosure type	Closed
Continuous power handling (IEC - Long Term)	80 Watt
Peak power capacity (IEC - Short Term)	160 Watt
Sensitivity (2.83 V / 1 m)	88 dB
Minimum amplifier output power recommended	10 Watt
Maximum sound pressure level	105 dB/1m
Impedance	4 - 8 Ohm
Frequency range from/to	150 - 20000 Hz
Crossover frequency internal switch	3400 Hz
Crossover frequency to Woofer (recommended)	150 - 180 Hz
Tweeter (number per enclosure)	1
Tweeter (diameter)	19.00 mm
Tweeter (material)	silk
Midrange driver (number per enclosure)	2
Midrange driver (diameter)	80.00 mm
Midrange driver (material)	coated cellulose
Miscellaneous	high excursion driver
Enclosure material	structure - synthetic

Enclosure surface	impact-resistant lacquer, matte
Net internal volume	1.20 Litres
Diameter of the stand screw threads	6.00 mm
Keyhole plate mounted	Yes
Miscellaneous	strong walls minimize resonances
Maximum cable diameter	2.50 mm
Suitable for AV receiver	Yes
Miscellaneous	requires little power for high levels

Dimensions

Depth	9.50 cm
Width	22.60 cm
Height	10.00 cm
Weight	1.25 kg

T 8 Subwoofer

High-end active subwoofer, can be used either front- or down-firing



Speaker

Acoustic principle	1-Way-System
Downfire	Yes
Frontfire	Yes
Enclosure type	Bass reflex
Maximum sound pressure level	111 dB/1m
Frequency range from/to	33-200 Hz Hz
Woofers (number per enclosure)	1
Woofers (diameter)	200.00 mm
Woofers (material)	Aluminium
Enclosure type	Bass reflex, DPU
Enclosure material	MDF
Enclosure surface	Matte coated
Equalisation openings	1
Integrated stand	Yes
Miscellaneous	Reflection channel in DPU technology avoids flow noises, stable MDF housing structure with internal bracing
Suitable for AV receiver	Yes

Connections

Cinch input	1
-------------	---

Miscellaneous Suitable for installation directly on the wall

Electronics

Miscellaneous Can be wirelessly controlled

Lowest frequency (-3 dB) 37 Hz

Bass boost/EQ Yes

Input gain adjustment Yes

Frequency regulator (range) 37 - 200 Hz Hz

Level control Yes

Phase control Yes

Miscellaneous Can be used either front- or down-firing

Amplifier technology Class-D

Amplifier configuration 1.0

Amplifier channels 1

Power output capacity impulse
(peak) Bass 100 W

Power supply voltage 230 Volt volts

Standby-Function Yes

Standby-Power consumption 1 watt

Maximum power consumption 100 watt

Mains lead fixed Yes

Safety class 2

Fuse Yes

Storage for settings when disconnected Yes

Automatic on/off Yes

Dimensions

Depth 38.00 cm

Width 31.10 cm

Height 42.30 cm

Weight 11 kg
