



## Stunning Home Cinema Projector with FullHD 1080p, High 50,000:1 Contrast Ratio, and Dynamic 3D SRS WOW<sup>®</sup> Audio

### FEATURES

- Full HD 1080p (1920 x 1080) resolution with a display up to WUXGA(1920 x 1200)
- High brightness of 2,000 ANSI lumens and high 50,000:1 contrast ratio ensuring a crisp and sharp image
- DLP<sup>®</sup> DarkChip3<sup>™</sup> and BrilliantColor<sup>™</sup> technologies for optimal black levels and vibrant colorful images
- ISF<sup>®</sup> calibration compatibility for the best possible image quality
- Host of connectivity options including HDMI v1.4, VGA-in, S-video, component and composite
- Vertical len shift for greater installation flexibility and convenience
- High-efficiency lamp that last up to 7000 hours (in dynamic eco. mode)
- Dynamic 3D SRS WOW<sup>®</sup> Audio with built-in 10W speaker
- Crestron<sup>®</sup> RoomView<sup>™</sup> certified
- Top sided cover for convenient lamp replacement
- Auto search filtering to quickly locate input signal source
- Compatible with long HDMI and VGA cables for a maximum length up to 20 meters
- Easy control with full functioning remote control and direct access 9 key menu pad
- Integrated Closed Caption Decoding (CCD) automatically converts the audio portion of a tv's signal and displays it as subtitles on the projected screen
- Anti-theft security features include: Kensington<sup>®</sup> security slot, security bar, and PIN lock keypad



## An outstanding home cinema projector with ISF calibration

The H1186 with a Full HD 1080p resolution delivers 2,000 ANSI lumens of brightness with a high contrast ratio of 50,000:1. With the ISF calibration the H1186 is the perfect solution to fully enjoy the home entertainment experience. The projector benefits of a native 1080p resolution and includes the Texas Instruments' DLP® DarkChip3™ and BrilliantColor™ technologies ensuring dazzling and colorful images with deep blacks. Easy to set up and install, the H1186 features a vertical lens shift for greater installation flexibility. The projectors include ISF mode for both day and night calibration, the SRS WOW® audio sound technology to deliver a cinematic experience with deep and rich bass as well as a complete set of multimedia connectivity options such as HDMI v1.4, MHL inputs to allow users to connect their cable/satellite receiver, Blu-Ray disc player or video gaming console, as well as various I/O ports such as VGA, S-Video, component and composite video, 3D Sync, RS-232, and 12v trigger.

# H1186

## HOME CINEMA



## SPECIFICATIONS



<b>Display Type</b>	Single 0.65" DLP® Technology by TI
<b>Brightness</b>	2,000 ANSI Lumens
<b>Native Resolution</b>	1080p (1920 x 1080)
<b>Maximum Resolution</b>	WUXGA (1920 x 1200) @60Hz
<b>Contrast Ratio</b>	50,000:1
<b>Lamp Life and Type</b>	3,500/5,000/7,000 Hours (Normal/Eco/Dynamic Eco. Mode) 240W/190W
<b>Throw Ratio</b>	1.39 - 2.09:1
<b>Image Size (Diagonal)</b>	25.9" - 324.9"
<b>Projection Distance</b>	1.2 - 10m
<b>Projection Lens</b>	F=2.418-2.97, f=20.7-31.05mm
<b>Zoom Ratio</b>	1.5x
<b>Aspect Ratio</b>	16:9
<b>Offset (full image height)</b>	130%
<b>Keystone Correction</b>	Vertical +/- 40°
<b>Horizontal Frequency</b>	15, 31 ~ 91.4kHz
<b>Vertical Scan Rate</b>	24 ~ 30Hz, 47 ~ 120Hz
<b>3D Compatibility</b>	Yes (Via DLP® Link™, Blu-ray 3D)
<b>Audio</b>	10W (Mono) with SRS WOW® Dynamic 3D Audio
<b>Computer Compatibility</b>	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac
<b>Video Compatibility</b>	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
<b>I/O Connection Ports</b>	HDMI v1.4, MHL/HDMI v1.4, VGA-In, Component (YPbPr RCA x 3), S-Video, Composite Video, Audio-In (RCA L/R), Audio-In (Mini-Jack), Audio-Out (Mini-Jack), 12V-Trigger (Mini-Jack), RS-232C, 3D-Sync-Out, USB Power (5V, 1.5A), Mini-USB (Service)
<b>Security Solutions</b>	Kensington® Security Slot, Security Bar, Keypad Lock
<b>Dimensions (WxDxH)</b>	285 x 261 x 121.8 mm
<b>Weight</b>	3,15kg
<b>Noise Level</b>	33dB/29db (Normal /Eco. Mode)
<b>Power</b>	Supply: AC 100-240V, 50/60Hz Consumption: 290W (Normal Mode) 240W (Eco. Mode) <0.5W (Standby Mode)
<b>Warranty</b>	Standard: 3 years projector / 1 year on lamp or 1000 hours whichever comes first
<b>Standard Accessories</b>	AC Power Cord, HDMI Cable, Remote Control, Carry Case, Lens Cap, Documentation Kit
<b>Optional Accessories</b>	Replacement Lamp: 5811120355-SVV
<b>UPC</b>	813097020505

© Copyright 2015 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc.

DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.

Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands  
tel: +31 20 655 0960 | fax: +31 20 655 0999 | email: info@vivitek.eu