

Projection System	DLP
Native Resolution	SVGA, 800 x 600
Brightness (ANSI Lumens)	3300 ANSI Lumen
Contrast Ratio	15000:1
Lens	F=2.46-2.66, f=21.8-25.6
Aspect Ratio	Native 4:3 (5 aspect ratio selectable)
Throw Ratio	1.94-2.32
Projection Size	30"~300"
Zoom Ratio	1.2x
Projection Offset**	Vertical: 106%±5% (Full image height)
Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200)*RB = Reduced blanking
3D Compatibility	Frame Sequential: Up to 60Hz 720p Frame Packing: Up to 24 Hz 1080p Side by Side: Up to 24Hz 1080p Top Bottom: Up to 60Hz 1080p
Horizontal Frequency	15K-102KHz
Vertical Scan Rate	23-120Hz
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM
Weight	5.24 lbs (2.38 Kg)
Dimensions (W x H x D mm)	332.4 x 99 x 241.3 mm
Interface	Computer in (D-sub 15pin) x2 *integrate with component HDMI x2 Monitor out x 1 Composite Video in (RCA) x 1 S-Video in x 1 Audio in (Mini Jack) x 1 Audio out (Mini Jack) x 1 Speaker 2W x 1 USB (Type mini B) x 1 RS232 (DB-9pin) x 1 IR Receiver x1 (Front)
Power Consumption	260W(Max), 252W(Normal), 211W(Eco), Standby <0.5W
Power Supply	AC100 to 240V, 50 to 60 Hz
DMD type	DC3
Light Source	UHP 203W
Light Source Life*	4500/6000/10000 hours
Noise Level	32/29 dBA (Normal/Economic mode)
Security	Security bar / Kensington Security Slot
On-Screen Display Languages	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)
Accessories (Standard)	Remote Control w Battery (5J.JG706.001) Warranty Card (by region) Power Cord (by region) VGA cable QSG (4J.JG701.001)

Accessories (Optional)	Spare Lamp Kit (5JJG705.001) 3D Glasses (5JJ9H25.002) Ceiling mount (5JJAM10.001) Carry Bag (5JJ4R09.001)
Environmental Notice	Lamp in this product contains mercury. To dispose of the product or used lamps, consult your local environment authorities for regulations or see www.lamprecycle.org .

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.