

TX-NR676E 7.2-Channel Network A/V Receiver











































Silken Power from an Amp with the Lot

Drive a full-scale surround system with effortless clarity. This thoroughbred A/V receiver streamlines access to app-based music, on-demand TV, games, and more. Linking your 4KTV and up to seven media players over HDMI®, the TX-NR676E processes all the popular Hi-Res and object-based audio codecs while Dynamic Audio Amplification boosts sound flawlessly for an adrenalin-pumping cinema experience. Future-focused, the receiver plays almost any audio accessible to your mobile or PC over dual-band Wi-Fi®, and comes with Chromecast built-in*, FlareConnect***, and DTS Play-Fi®*, which make multi-room audio very simple. It's a receiver with the lot, and one of the best sounding amps available. * Firmware update required.

HIGHLIGHTS

- Supports 5.2.2-Channel Dolby Atmos $^{\otimes}$ and DTS:X $^{\otimes}$ Playback
- 165 W per Channel
- HDMI 7 In (I Front*1) / Main Out, and Sub Out*2 Supporting 4K/60 Hz, HDR10, Dolby Vision™, BT.2020, and HDCP 2.2 Pass-through
- Dynamic Audio Amplification with 4-Ohm Speaker-driving Capability
- 384 kHz/32-bit DAC and VLSC[™] Filtering for Superior Clarity
- Ready for Chromecast built-in*3 and DTS Play-Fi*3
- Dual-band Wi-Fi, AirPlay, Spotify®, TIDAL, Deezer,
- FlareConnect^{™+3} Wireless Multi-room Audio

ADVANCED FEATURES

- Supports 5.2.2-Channel Dolby Atmos Playback and Dolby Surround Upmixing
- DTS:X Object-based Audio Reproduction and DTS Neural:X™ 3D Upmixing
- Dolby Surround 3D Upmixing Solution for Multichannel Surround Formats
- AccuEQ Room Acoustic Calibration with AccuReflex Phase Alignment for Dolby Atmos-enabled Speaker • Ready for Onkyo Controller App Integrated Multi-room Intuitive Operation^{¥5}
- Stable Dual-band 5 GHz/2.4 GHz Wi-Fi® Connectivity
- Features Chromecast built-in Wireless Audio Streaming Technology
- Supports DTS Play-Fi Multi-room Audio
- AirPlay Audio Streaming from iTunes and iPad, iPhone, and
- Supports Hi-Res Audio Including DSD 5.6 MHz/2.8 MHz*6, 192 kHz/24-bit FLAC, WAV, AIFF, and ALAC, and Dolby®

- Supports Spotify, TIDAL, TuneIn, and Deezer Services
- FlareConnect Multi-room Audio Distribution to Compatible Components and Speakers
- Powered Zone 2 Speaker Outputs and Zone 2 Line Output with Dedicated DAC Supporting Digital[®] and Analog Audio Playback
- Bluetooth® Wireless Technology for Mobiles, Laptops, and PCs (Version 4.1 + LE, Profile: A2DP v1.2, AVRCP v1.3)
- Advanced Music Optimizer Improves Compressed Digital Audio Quality, Including Bluetooth Audio Supports for Front L/R Channel Bi-Amping in 5.2-Ch
- Speaker Layout
- 480i De-interlacing (480i to 480p) via HDMI for Legacy

AMPLIFIER FEATURES

- 165 W/Ch (6 Ω, I kHz, I% THD, I Channel Driven, IEC)
- · Dynamic Audio Amplification System Delivers Thrilling Stereo and Multichannel Performance
- High-current Power to Drive Large Speakers with
- H.C.P.S. (High Current Power Supply) Transformer
- VLSC (Vector Linear Shaping Circuitry) High-frequency Noise Removal (Front L/R Channels)
- · Non-Phase-Shift Amplification Circuitry for Clarity and Detail
- Discrete Output Stage Circuitry for Low Distortion

PROCESSING FEATURES

- Dolby Atmos and DTS:X Reproduction (5.2.2 Channels)
- HDMI Support for 4K/60 Hz, HDR10, Dolby Vision, 3D, Audio Return Channel, DeepColor™, x.v.Color™, LipSync, Dolby Atmos, Dolby TrueHD, DTS:X, DTS-HD Master Audio™, DSD, DVD-Audio, Super Audio CD (SACD), Multichannel PCM, and CEC
- High-grade AKM (AK4458) 384 kHz/32-bit Multichannel DAC
- PLL (Phase Locked Loop) Jitter-Cleaning Circuit Technology for S/PDIF Audio
- 32-bit Digital Signal Processing
- DSP Modes for Gaming: Rock, Sports, Action, and RPG
- Theater-Dimensional Virtual Surround Function
- Enjoy Pristine Reproduction of Audio-only Sources in Pure Audio Mode

- Direct Mode for Audio Reproduction Close to Original
- Tone Controls (Bass/Treble) for Front L/R Channels

CONNECTION FEATURES

- 7 HDMI Inputs (I Front) and 2 Outputs (I Main Out, I Sub Out)
- Powered USB Port (5 V, I A) for Audio Playback
- 2 Composite Video Inputs
- 2 Component Video Inputs
- 3 Digital Audio Inputs (2 Optical and I Coaxial)
- 6 Analog Audio Inputs (6 Coaxial), I Stereo Analog Input (3.5 mm, Front)
- Phono Input (MM) and Equalizer for Turntable
- 2 Subwoofer Pre-Outs
- Headphone Jack (6.35 mm, Front)
- Speaker Posts with Screw Knobs
- Speaker Setup Mic Input (Front)

OTHER FEATURES

- · Crossover Adjustment for Each Channel (40/50/60/70/80/90/100/120/150/180/200 Hz)
- A/V Sync Control (Up to 500 ms in 5 ms Steps at 48 kHz)
- Graphical User Interface with Overlaid On-Screen Display (OSD) via HDMI
- Quick Setup Guide via GUI and Easy Connection Diagram on
- Large Input Selector Buttons
- Economical HDMI Pass-through and Network Standby Functions IP Control via LAN for Home Automation Systems
- 3-Mode Display Dimmer (Normal/Dim/Dimmer)
- 40 FM/AM Random Presets
- Full-sized Simple Remote Control

* Full-sized Simple memore Lontrol
*I HDMI front Input does not support 4K/60p/4:4-4/24-bit video, HDR10, Dolby
Vision, or BT.2020. *2 HDMI Sub Out does not support ARC or CEC. *3 Requires a
firmware update: 44 Availability of services may vany with region Please confirm before
purchase. Subscription may also be required. *5 For IOS and Android" devices. Please
check App Stare or Google Play for device and OS requirements. *6 DSD not supported
over wireless. LAN. *7 Dolby TrueHD playback via USB input only. *8 Audio via HDMI inputs excluded

Unlock Dolby Atmos® and DTS:X® Playback

Object-based soundtracks allow independently mixed sound to play through any speaker in your system. Effects move all around as they do in real life, so you experience 5.2.2-channel Dolby Atmos or DTS:X formats as the director intended. DTS Neural: $X^{\mathbb{N}}$ identifies spatial effects in multichannel soundtracks and upmixes for 3D playback, while DTS:X offers independent dialog volume control for movies. Dolby Surround is also

included to upmix legacy multichannel formats for playback in a Dolby Atmosenabled environment.



Onkyo Controller Supports Next Generation Network Audio

Onkyo Controller app collects streaming services and network-attached audio into an intuitive interface. Control playback, navigate internet services, and distribute audio all over the home with ease.




Chromecast built-in

Music Made Easy with Chromecast built-in*

Stream any music from your smartphone, laptop, or PC to the TX-NR676E with ease. Control playback with Chromecastenabled apps you know and love

from your iPhone, iPad, Android¹¹ phone or tablet, Mac® or Windows® laptop, or Chromebook™



DTS Play-Fi allows you to enjoy high-quality music from connected online services, networked media servers, and your device library over Wi-Fi® to any number of compatible products using the Onkyo Music Control App for iPad, iPhone, and Android™ smartphones/tablets. DTS Play-Fi can synchronize the music in every room. Each member of your family can use their own device to listen to their own music in their room or group of rooms. DTS Play-Fi lets you easily

structure a comprehensive multi-room ecosystem that satisfies virtually any need. For more information, visit www.play-fi.com.



* Enabled with a firmware update.

Wi-Fi®, AirPlay, Spotify®, and Bluetooth®

Selectable 5 GHz/2.4 GHz Wi-Fi assures stable connectivity so you can enjoy smooth streaming over AirPlay, the Spotify app, and the local network. Bluetooth wireless technology also provides quick and simple wireless streaming from your choice of music application.









Internet Radio and Streaming Services

TIDAL, Deezer, and TuneIn are baked into the GUI, making it easy to select from a huge range of music and radio programs using Onkyo Controller







FlareConnect™ Wireless Multi-room Audio

FlareConnect* shares audio from network and external audio input sources between compatible components. Enjoy effortless multi-room playback of LP records, CDs, network music services, and more with supported components and speaker systems. Music selection, speaker grouping, and playback management across the home are built into the Onkyo Controller** app.



Sharing audio from external inputs is enabled with a future firmware update External audio inputs supporting FloreConnect may differ depending on model. Please consult individual product specification for more information. ** Download free from the App Store or Google Play.

4K HDR, BT.2020, 4K/60 Hz, and HDCP 2.2 Support

Six rear HDMI® inputs support pass-through of 4K HDR in both HDR10 and Dolby Vision™ formats; the BT.2020 4K Video Standard, 4K/60 Hz video playback; and HDCP 2.2 for premium content. Further, front HDMI is available for easy connection of a video camera or game console, while a rear Sub Output is ideal for connecting a projector.



HDCP 2.2

Powerful Amplification for Dynamic Sound

High current power is proven by the ability to drive four-ohm speaker loads, which will severely test the strongest multichannel amplifier. Heaps of muscle means superior control for improved clarity and transient response, restoring energy to stereo and multichannel sound. Further, VLSC1 eliminates pulse-noise for optimal playback.

Graphical User Interface with Easy Setup

With your speakers and media players connected, plug in the AccuEQ mic and let the GUI guide you through initial setup, from speaker calibration (including AccuReflex phase correction for Dolby Atmos-enabled speakers) through to network connection. The refined interface makes control simple and enjoyable

Powered Zone 2 and Zone 2 Lineouts

Powered Zone 2 speaker outputs let you send amplified network, S/PDIF, or analog audio sourced to a pair of speakers in another room. Line outputs can connect your home cinema sources to a separate hi-fi system. Manage playback using Onkyo Controller

Requires a firmware update

SPECIFICATIONS Amplifier Section Power Output 165 W/Ch (6 Ω, 1 kHz, 1% THD, All Channels I Channel Driven, IEC) 240 W (3 Ω, Front) 210 W (4 Ω, Front) 120 W (8 Ω, Front) Dynamic Powe Distortion + Noise) 0.08% (20 Hz–20 kHz, Half Power) THD+N (Total Harmonic Damping Factor Less than 54 (Front, 1 kHz, 8 Ω) Input Sensitivity and Impedance 200 mV/47 k0 (Line) 3.5 mV/47 kΩ (Phono) Rated RCA Output Level and Impedance I V/470 Ω (Subwoofer Pre Out) 200 mV/2.3 kΩ (Zone Line Out) Frequency Response Tone Control 10 Hz-100 kHz/+1 dB, -3 dB (Direct Mode) ±10 dB, 90 Hz (Bass) ±10 dB, 7.5 kHz (Treble) 106 dB (Line, IHF-A) 80 dB (Phono, IHF-A) Signal-to-Noise Ratio Speaker Impedance 4 Ω–16 Ω Video Section Input Sensitivity/Output Level and Impedance I.0 Vp-p/75 Ω (Component Y)

11000	1.0 1p p//3 11 (COMPONENT 1)
	0.7 Vp-p/75 Ω (Component PB/CB, PR/CR)
	I.0 Vp–p/75 Ω (Composite)
Tuner Section	
Tuning Frequency Range	
FM	87.5 MHz-108 MHz
AM	522 kHz-1,611 kHz
	530 kHz-1,710 kHz
FM/AM Preset Memory	
General	
Power Supply	AC 220-240 V~, 50/60 Hz
Power Consumption	570 W
No-Sound Power Consun	nption
	60 W
Standby Power Consump	tion
	0.15 W
Dimensions (W x H x D)	435 x 173.5 x 378 mm
Weight	10.0 kg
CARTON	

Dimensions (W x H x D)	539 x 260 x 450 mm
Weight	12.5 kg

Supplied Accessories

- Indoor FM antenna AM loop antenna Speaker setup microphone Quick Start Guide Basic Manual Remote controller AAA (R03) batteries x 2



Due to a policy of continuous product improvement, Onlyo reserves the right to change specifications and appearance without notice. Dolby, Dolby Atmos, Dolby Surround, Dolby Vision, and the double-D symbol are trademarks of Dolby Laboratories. For DTS patients, see http://jacetns.cts.ccom. Manufactured under license from DTS Licensing Limited DTS, the Symbol, DTS and the Psychiate DTSX logo, Play-Fi, and the Psy-Fi logo are registered trademarks or trademarks or prostered to prostered trademarks or proste



71/01) 71/5 03/17