



Top of the class

Columa 300 Mk2 "5.1-Set L"

This elegant and slim column speaker set with powerful subwoofer lets you experience your movies and music on a whole new level.

Highlights:

- 5.1 home cinema set with 4 standing speakers made from aluminium
- Perfect for movies, music and gaming
- With short or long columns, comes in set L, M or S
- 2-way system with two mid-range drivers
- Powerful subwoofer that can be used front- or down-firing and can be operated wirelessly

Included components

- 4 x Column Speaker CL 302 FR (pc.)
- 1 x Center Speaker CL 302 C
- 1 x T 8 Subwoofer

Specifications

Centre Speaker CL 302 C:

Speaker	Acoustic principle	2-Way-System
	Enclosure type	Closed
	Continuous power handling (IEC - Long Term)	80 Watt
	Peak power capacity (IEC - Short Term)	100 Watt
	Sensitivity (2.83 V / 1 m)	84 dB
	Minimum amplifier output power recommended	20 Watt
	Maximum sound pressure level	96 dB/1m
	Impedance	4 - 8 Ohm
	Frequency range from/to	120 - 20000 Hz
	Crossover frequency to Woofer (recommended)	150 Hz
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	19.00 mm
	Tweeter (material)	Fabric
	Bass/Midrange driver (number per enclosure)	2
	Bass/Midrange driver (diameter)	70.00 mm
	Bass/Midrange driver (material)	Cellulose, coated
	Enclosure material	Aluminium
	Enclosure surface	Matte, metallic lacquer
	Net internal volume	2.90 Litres
	Wall mounting brackets	Yes
	Keyhole plate mounted	Yes
	Magnetic shielding	Yes
	Terminal clamps	Screw terminals, gold plated
	Maximum cable diameter	2.50 mm
	Suitable for AV receiver	Yes
Dimensions	Depth	12.60 cm
	Width	39.20 cm
	Height	8.50 cm
	Weight	1.40 kg

Column Speaker CL 302 FR (pc.):

Speaker	Continuous power handling (IEC - Long Term)	80 Watt
	Peak power capacity (IEC - Short Term)	100 Watt
	Sensitivity (2.83 V / 1 m)	84 dB
	Minimum amplifier output power recommended	20 Watt
	Maximum sound pressure level	96 dB/1m
	Impedance	4 - 8 Ohm
	Frequency range from/to	120 - 20000 Hz
	Crossover frequency to Woofer (recommended)	150 Hz
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	19.00 mm
	Tweeter (material)	Fabric
	Midrange driver (number per enclosure)	2
	Midrange driver (diameter)	70.00 mm
	Midrange driver (material)	Cellulose, coated
	Bass/Midrange driver (material)	Cellulose, coated
	Acoustic principle	2-way
	Enclosure type	Closed
	Enclosure material	Aluminium
	Enclosure surface	Matte, metallic lacquer
	Net internal volume	2.90 Litres
	Magnetic shielding	Yes
	Terminal clamps	Gold-plated screw terminals
	Maximum cable diameter	2.50 mm
	Suitable for AV receiver	Yes
Dimensions	Depth	12.60 cm
	Width	8.50 cm
	Height	112.00 cm
	Weight	4.50 kg

T 8 Subwoofer:

Speaker	Acoustic principle	1-Way-System
	Downfire	Yes
	Frontfire	Yes
	Enclosure type	Bass reflex
	Maximum sound pressure level	111 dB/1m
	Frequency range from/to	33-200 Hz Hz
	Woofer (number per enclosure)	1
	Woofer (diameter)	200.00 mm
	Woofer (material)	Aluminium
	Enclosure type	Bass reflex, DPU
	Enclosure material	MDF
	Enclosure surface	Matte coated

	Equalisation openings	1
	Integrated stand	Yes
	Miscellaneous	Reflection channel in DPU technology avoids flow noises, stable MDF housing structure with internal bracing
	Suitable for AV receiver	Yes
Connections	Cinch input	1
	Miscellaneous	Suitable for installation directly on the wall
Electronics	Miscellaneous	Can be wirelessly controlled
	Lowest frequency (-3 dB)	37 Hz
	Bass boost/EQ	Yes
	Input gain adjustment	Yes
	Frequency regulator (range)	37 - 200 Hz Hz
	Level control	Yes
	Phase control	Yes
	Miscellaneous	Can be used either front- or down-firing
	Amplifier technology	Class-D
	Amplifier configuration	1.0
	Amplifier channels	1
	Power output capacity impulse (peak) Bass	100 W
	Power supply voltage	230 Volt volts
	Standby-Function	Yes
	Standby-Power consumption	1 watt
	Maximum power consumption	100 watt
	Mains lead fixed	Yes
	Safety class	2
	Fuse	Yes
	Storage for settings when disconnected	Yes
Dimensions	Automatic on/off	Yes
	Depth	38.00 cm
	Width	31.10 cm
	Height	42.30 cm
	Weight	11 kg