



Film buff

Cubycon Impaq Easy

The Cubycon Impaq Easy is the complete system for discerning audio fans who don't want to compromise on floor space. It combines an AV receiver and Blu-ray player in one compact unit. The Easy version includes a smaller subwoofer.

Highlights:

- Ready-to-play 5.1 Blu-ray complete system with high-end 2-way aluminium micro loudspeakers
- Integrated slim-line Blu-ray A/V receiver with HD audio, 3D, Bluetooth streaming and DLNA
- Comes with matching components and everything you need for immediate play, including high-quality cable set
- High system performance for an immersive audio performance for films, music and games
- Compact, wireless subwoofer

Included components

- 4 x Satellite Speaker CUB 2 FR 15 (pcs.)
- 1 x Centre Speaker CUB 2 C 15
- 1 x Impaq 8000 Blu-ray Receiver
- 1 x power cable
- 1 x FM antenna for IP 8000 BR
- 1 x IP 8000 RC Remote Control
- 1 x T 6 Subwoofer
- 1 x HDMI-Cable 1.4 1.5m - C1515V
- 1 x 30m Speaker Cable 1.0mm² - C1030S

Specifications

Impaq 8000 Blu-ray Receiver:

Connections	4K UHD Upscale	Yes
	Bluetooth	Yes
	Bluetooth	Yes
	Wifi	Yes
	Wifi	Optional
	LAN	Yes
	LAN	1
	NFC	Yes
	Digital inputs coaxial	1
	Digital inputs optical	1
	Cinch input stereo	1
	Cinch output stereo	1
	Bass driver output	1
	High level speaker outputs	5
	Video inputs- HDMI	3
	Video inputs- HDMI	Yes
	HDMI Version	1.4b
	Miscellaneous	HDMI 3D
	Video outputs - HDMI	1
	Video outputs - HDMI	Yes
	HDMI Version	1.4b
	USB 2.0	2
Playback	ASF	Yes
	Dolby TrueHD	Yes
	DTS-HD Master Audio	Yes
	Dolby Digital	Yes
	DTS	Yes

MP2	Yes
MP3	Yes
WMA	Yes
WAV	Yes
AAC	Yes
FLAC	Yes
OGG	Yes
HDCD	Yes
M4A	Yes
Apple Lossless	Yes
Dolby Digital Plus	Yes
Dolby Pro Logic	Yes
Dolby Pro Logic II	Yes
Dolby Headphone	Yes
JPEG	Yes
GIF	Yes
BMP	Yes
FLV	Yes
MPEG1	Yes
MPEG2	Yes
MPEG4	Yes
DivX	Yes
DivX HD	Yes
RealMedia	Yes
Xvid	Yes
AVC/H.264	Yes
WMV	Yes
MKV	Yes
CD-Audio	Yes
VCD	Yes
SVCD	Yes
DVD-Video	Yes
DVD-Audio	Yes
Blu-ray	Yes
BDMV	Yes
BDAV	Yes
CD	Yes
DVD	Yes
Blu-ray	Yes
CD-R	Yes
CD-RW	Yes

	DVD-R	Yes
	DVD+R	Yes
	DVD-RW	Yes
	DVD+RW	Yes
	DVD-RAM	Yes
	BD-R	Yes
	BD-RE	Yes
Radio	Radio present	Yes
	Channel memory slot - FM	30
	RDS	Yes
	FM - UKW	Yes
Electronics	10-Mbit/s Ethernet	Yes
	10/100-Mbit/s Ethernet	Yes
	Miscellaneous	DLNA
	Amplifier technology	Class-D
	Amplifier configuration	5.0
	Amplifier channels	5
	Power output capacity impulse (peak) Satellite	100 W
	Power output capacity sinus (RMS) Satellite	75 W
	Power supply voltage	230 Volt volts
	Standby-Function	Yes
	Standby-Power consumption	0.40 watt
	Maximum power consumption	700 watt
	Mains cable - IEC connector (non-heating device)	Yes
	Safety class	2
	Storage for settings when disconnected	Yes
	Automatic on/off	Yes
	Display	Yes
	OSD	Yes
	Integrated DSP	Yes
	Audio-Digital-Analog-Converter	Texas Instruments
	Integrated DD/dts/PLII-Decoder	Yes
	Integrated True HD/dts HD/DD/dts/PLII-Decoder	Yes
	Remote control	Infrared
	Power source	AAA
Dimensions	Depth	36.00 cm
	Width	40.00 cm
	Height	8.00 cm
	Weight	4.80 kg

Satellite Speaker CUB 2 FR 15 (pcs.):

Speaker	Acoustic principle	2-Way-System
	Enclosure type	Bass reflex
	Continuous power handling (IEC - Long Term)	100 Watt
	Peak power capacity (IEC - Short Term)	140 Watt
	Sensitivity (2.83 V / 1 m)	90 dB
	Minimum amplifier output power recommended	20 Watt
	Maximum sound pressure level	100 dB/1m
	Impedance	4 - 8 Ohm
	Frequency range from/to	200 - 20000 Hz
	Crossover frequency internal switch	5000 Hz
	Crossover frequency to Woofer (recommended)	150 - 200 Hz
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	20.00 mm
	Tweeter (material)	Seide
	Midrange driver (number per enclosure)	2
	Midrange driver (diameter)	80.00 mm
	Midrange driver (material)	Cellulose, coated
	Enclosure material	Aluminium
	Enclosure surface	Anodised
	Equalisation openings	2
	Equalisation openings (pos.)	Back
	Net internal volume	1.20 Litres
	Wall mounting brackets	Yes
	Keyhole plate mounted	Yes
	Magnetic shielding	Yes
	Terminal clamps	Gold-plated screw terminals
	Suitable for banana plug	Yes
	Maximum cable diameter	4.00 mm
	Suitable for AV receiver	Yes
Connections	High level speaker outputs	1
Dimensions	Depth	9.70 cm
	Width	18.80 cm
	Height	9.50 cm
	Weight	1.40 kg

Centre Speaker CUB 2 C 15:

Speaker	Acoustic principle	2-Way-System
	Enclosure type	Bass reflex
	Continuous power handling (IEC - Long Term)	100 Watt
	Peak power capacity (IEC - Short Term)	140 Watt
	Sensitivity (2.83 V / 1 m)	90 dB
	Minimum amplifier output power recommended	20 Watt

	Maximum sound pressure level	100 dB/1m
	Impedance	4 - 8 Ohm
	Frequency range from/to	200 - 20000 Hz
	Crossover frequency internal switch	5000 Hz
	Crossover frequency to Woofer (recommended)	150 - 200 Hz
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	20.00 mm
	Tweeter (material)	Seide
	Midrange driver (number per enclosure)	2
	Midrange driver (diameter)	80.00 mm
	Midrange driver (material)	Cellulose, coated
	Enclosure material	Aluminium
	Enclosure surface	Anodised
	Equalisation openings	2
	Equalisation openings (pos.)	Back
	Net internal volume	1.20 Litres
	Wall mounting brackets	Yes
	Keyhole plate mounted	Yes
	Magnetic shielding	Yes
	Terminal clamps	Gold-plated screw terminals
	Suitable for banana plug	Yes
	Maximum cable diameter	4.00 mm
	Suitable for AV receiver	Yes
Connections	High Level loudspeaker inputs	1
Dimensions	Depth	9.70 cm
	Width	9.50 cm
	Height	18.80 cm
	Weight	1.40 kg

T 6 Subwoofer:

Speaker	Acoustic principle	1-Way-System
	Downfire	Yes
	Enclosure type	Bass reflex
	Maximum sound pressure level	104 dB/1m
	Frequency range from/to	33 - 200 Hz Hz
	Woofer (number per enclosure)	1
	Woofer (diameter)	165.00 mm
	Woofer (material)	Coated cellulose
	Enclosure type	Bass reflex
	Enclosure material	MDF
	Enclosure surface	Matte laminate
	Equalisation openings	1

	Equalisation openings (pos.)	Bottom
	Net internal volume	20 Litres
	Integrated stand	Yes
Connections	Miscellaneous	Subwoofer receives audio signal wirelessly
Electronics	Lowest frequency (-3 dB)	33 Hz
	Amplifier technology	Class-D
	Amplifier channels	1
	Power output capacity impulse (peak) Bass	90 W
	Power output capacity sinus (RMS) Bass	60 W
	Power supply voltage	230 Volt volts
	Standby-Function	Yes
	Standby-Power consumption	0.40 watt
	Maximum power consumption	120 watt
	Safety class	2
	Automatic on/off	Yes
Dimensions	Depth	38.00 cm
	Width	21.00 cm
	Height	40.00 cm
	Weight	8.57 kg