

ower speaker UL 40 Active Mk2 18 (pcs.)

Aktiver Standlautsprecher mit integriertem Verstärker, Bedienpanel und Display



Speaker

Enclosure type	Bass reflex
Frequency range from/to	39-20000 Hz
Tweeter (number per enclosure)	1
Tweeter (diameter)	25.00 mm
Tweeter (material)	Fabric, chrome phase plug
Midrange driver (number per enclosure)	1
Midrange driver (diameter)	165.00 mm
Midrange driver (material)	Kevlar / Fibreglass, chrome phase plug
Woofers (number per enclosure)	2
Woofers (diameter)	165.00 mm
Woofers (material)	Fibreglass + cellulose, coated
Enclosure material	MDF

Enclosure surface	Laminated, matte
Removable front cover	Yes
Spikes prepared	Yes
Integrated stand	Yes
Suitable for banana plug	Yes
Maximum cable diameter	4.00 mm

Connections

Audio inputs- HDMI	1
AUX	Yes
2.0 USB sound card	Yes
Bluetooth aptX	Yes
Micro USB B	Yes
Bluetooth	Yes
Bluetooth	supports apt-X
Digital inputs optical	1
Miscellaneous	HDMI port supports ARC/CEC
Cinch input stereo	1
Bass driver output	1

Playback

Dolby Digital Yes

Dolby Pro Logic Yes

Electronics

Total power output capacity (RMS) 260 Watt

Adjustable sound settings Yes

Amplifier technology Class-D

Amplifier channels 2

Power output capacity impulse (peak) Satellite 130 W

Performance measured by (Ohm) 4

Power supply voltage 230 volts

Standby-Function Yes

Remote control Infrared

Dimensions

Depth 32.00 cm

Width 21.50 cm

Height 106.50 cm

Weight 21.20 kg

Miscellaneous Dimensions base plate depth: 35.2 cm width 24.7 cm

UL 40 Mk3 18 tower speaker (pcs.)

High-end Hi-Fi standing speakers



Speaker

Acoustic principle	3-Way-System
Enclosure type	Bass reflex
Continuous power handling (IEC - Long Term)	120 Watt
Peak power capacity (IEC - Short Term)	200 Watt
Sensitivity (2.83 V / 1 m)	87 dB
Maximum sound pressure level	108 dB/1m
Impedance	4-8 Ohm
Frequency range from/to	45 - 20,000 Hz
Tweeter (number per enclosure)	1
Tweeter (diameter)	25.00 mm
Tweeter (material)	Fabric weaving
Midrange driver (number per enclosure)	1
Midrange driver (diameter)	165.00 mm
Midrange driver (material)	Kevlar, chrome phase plug

Woofers (number per enclosure)	2
Woofers (diameter)	165.00 mm
Woofers (material)	Fibreglass
Miscellaneous	Hochtöner mit Phase Plug, Material: Stahl
Enclosure material	MDF
Enclosure surface	Laminated
Equalisation openings	2
Equalisation openings (pos.)	Rear side
Removable front cover	Yes
Net internal volume	54 Litres
Spikes prepared	Yes
Integrated stand	Yes
Terminal clamps	Screw terminal, gold-plated
Suitable for banana plug	Yes
Bi-Amping/Bi-Wiring	Yes
Maximum cable diameter	4.00 mm
Suitable for AV receiver	Yes

Dimensions

Depth 32.00 cm

Width 21.50 cm

Height 106.50 cm

Weight 20 kg

Miscellaneous Base plate dimensions: depth: 35 cm / width: 25 cm

Effekt satellite speakers (pcs)



Speaker

Acoustic principle 2-Way-System

Enclosure type Closed

Frequency range from/to 120 - 20000 Hz

Tweeter (number per enclosure) 1

Tweeter (diameter) 19.00 mm

Midrange driver (number per enclosure) 1

Midrange driver (diameter) 76.00 mm

Enclosure material Plastic

Enclosure surface Housing: silk matte / grille: glossy

Wall mounting brackets Yes

Keyhole plate mounted Yes

Miscellaneous Compatible speaker stands: Teufel AC 1001

Electronics

Amplifier technology Class-D

Amplifier channels 2

Output performance amplifier: Satellites 35 W

Standby-Function Yes

Standby-Power consumption 0.50 watt

Storage for settings when disconnected Yes

Automatic on/off Yes

Miscellaneous 4-metre long power cable

Dimensions

Depth 11.20 cm

Width 11.20 cm

Height 15.30 cm

Weight 0.96 kg
