

## **DW265** EDUCATION PROJECTORS



## Versatile Portable Projector with High Brightness



# **FEATURES**

- DLP® technology with BrilliantColor<sup>™</sup> for vibrant and rich picture quality
- 3,500 ANSI lumens of brightness and 15,000:1 contrast ratio for clear, crisp and bright presentations
- WXGA (1280 x 800) native resolution and support up to maximum WUXGA (1920x1200) resolution
- Dual-HDMI inputs for high definition content with the same high quality
- Compact and lightweight at 2.6kg for easy portability
- A long lamp life up to 10,000 hours for low Total Cost of Ownership (TCO)
- Audio ready with built-in 2 watt audio speaker, audio-in and audio-out ports









#### From meeting room to presentations anywhere on the road

The DW265 is a native WXGA digital projector from Vivitek. It features DLP<sup>®</sup> and BrilliantColor<sup>™</sup> technologies to display distinct, vibrant images in a widescreen format. The Vivitek DW265 features numerous connectivity options including two HDMI v1.4, a brightness level of 3,500 ANSI Lumens, and a 15,000:1 contrast ratio. With its light weight and compact form this is a short throw projector for easy installation that will fit any budget.



### **DW265 SPECIFICATIONS**

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	3500 ANSI Lumens
	Native Resolution	WXGA (1280 x 800)
	Max. Supported Resolution	WUXGA (1920 x1200) @60Hz
	Native Aspect Ratio	16:10
	Contrast Ratio	15,000:1
	Keystone Correction	Vertical: +/-40°
Optical	Throw Ratio	1.55 - 1.86 : 1
	Zoom Ratio	1.2x
	Image Size (Diagonal)	40" - 240"
	Projection Distance	1.3 - 9.6 m
	Projection Lens	F = 2.46 - 2.66, f = 21.8 - 25.6 mm
	Offset (Based on Full Image Height)	103.6%
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x2), HDMI (x2), S-Video, Composite Video, Audio-I (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RS-232, USB miniB (Service)
General	Dimensions (W x D x H)	332 x 243 x 107 mm
	Weight	2.6 kg
	Lamp Life and Type	5,000 / 7,000 / 10,000 Hours (Normal / Eco. / Dynamic Eco. Mode), 203W
	Speakers	2 W
	Standard Accessories	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region Remote Controller (with battery), AC Power Cord
	<b>Optional Accessories</b>	Spare Lamp P/N (XX5050002200), Remote Control P/N (XX5040005400), Carrying Case P/N (XX3520000800)
	Warranty	Entry Warranty: 2 years projector / 1 year on lamp or 1.000 hours whicheve comes first, Education Warranty: 5 years projector / 3 years on lamp or 2.000 hours whichever comes first
	UPC Code	813097023339

© Copyright 2017 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc.

DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.