



## Full metal package

### Cinesystem Trios "5.1-Set M"

The Cinesystem Trios is a true surround sound system. The two short rear speakers in the Set M configuration are controlled wirelessly. Inconspicuous, elegant and acoustically captivating, the set turns your living room into a real home cinema.

#### Highlights:

- Plug-&-play 5.1 soundbar system with flat subwoofer for top quality sound
- Integrated, high-performance centre speaker for excellent speech intelligibility
- Wireless flat subwoofer can be slid under a sofa or even wall mounted
- Wireless rear speakers make setup easy, available as Set M or L
- Powerful surround sound thanks to a total of 465-Watt power output, 22 drivers, 2-way system and Dynamore® technology

## Included components

- 1 x Soundbar CS 42
- 1 x power cable
- 1 x Remote Control CS 42 RC
- 2 x Satellite Speaker L 430 FCR (pcs.)
- 1 x Subwoofer T 4000 SW (without wireless module)
- 2 x RearStation Compact RX (pcs.)
- 1 x SubConnect MOD
- 1 x 15 m Speaker Cable 1.0mm<sup>2</sup> - C1015S

## Specifications

### Soundbar CS 42:

<b>Speaker</b>	Acoustic principle	2-Way-System
	Enclosure type	Closed
	Continuous power handling (IEC - Long Term)	45 Watt
	Peak power capacity (IEC - Short Term)	60 Watt
	Maximum sound pressure level	104 dB/1m
	Frequency range from/to	130 - 20000 Hz
	Tweeter (number per enclosure)	3
	Tweeter (diameter)	20.00 mm
	Tweeter (material)	Silk
	Midrange driver (number per enclosure)	6
	Midrange driver (diameter)	77.00 mm
	Midrange driver (material)	Coated cellulose
	Enclosure material	Aluminium
	Enclosure surface	Brushed aluminium
	Net internal volume	7 Litres
	Integrated stand	Yes
	Wall mounting brackets	Yes
	Keyhole plate mounted	Yes
<b>Connections</b>	Bluetooth aptX	Yes
	Bluetooth	Yes
	Bluetooth	Bluetooth 4.0 aptX
	NFC	Yes
	Digital inputs optical	1
	Stereo jack 3.5mm - in	1
	Bass driver output	1
	Video inputs- HDMI	1
	Video inputs- HDMI	Yes
	HDMI Version	1.4b

	Video outputs - HDMI	1
	Video outputs - HDMI	Yes
	Miscellaneous	HDMI CEC HDMI ARC 3D video support
	USB 2.0	per software update
<b>Playback</b>	DTS NEO:6	Yes
	Dolby Digital	Yes
	DTS	Yes
	Dolby Pro Logic	Yes
<b>Electronics</b>	Dolby Pro Logic II	Yes
	Dynamore®	Yes
	Amplifier technology	Class D
	Amplifier configuration	3.0
	Amplifier channels	6
	Power output capacity impulse (peak) Satellite	55 W
	Power output capacity sinus (RMS) Satellite	75 W
	Power supply voltage	230 volts
	Standby-Function	Yes
	Standby-Power consumption	0.40 watt
	Maximum power consumption	225 watt
	Safety class	2
	Storage for settings when disconnected	Yes
	Automatic on/off	Yes
	Display	Yes
	OSD	Yes
	Integrated DSP	Yes
	Audio-Digital-Analog-Converter	24 Bit/96 kHz Cirrus Logic
<b>Dimensions</b>	Remote control	Infrared
	Materials	Aluminium
	Depth	9.80 cm
	Width	115.00 cm
	Height	9.30 cm
	Weight	6.50 kg
	Miscellaneous	Total height with table stand is 11.70 cm

#### Satellite Speaker L 430 FCR (pcs.):

<b>Speaker</b>	Acoustic principle	3-Way-System
	Enclosure type	Closed
	Continuous power handling (IEC - Long Term)	70 Watt
	Peak power capacity (IEC - Short Term)	100 Watt
	Sensitivity (2.83 V / 1 m)	86 dB

	Minimum amplifier output power recommended	20 Watt
	Maximum sound pressure level	101 dB/1m
	Impedance	4-8 Ohm
	Frequency range from/to	135-20000 Hz
	Crossover frequency internal switch	450/2800 Hz
	Crossover frequency to Woofer (recommended)	120 Hz
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	19.00 mm
	Tweeter (material)	Fabric
	Midrange driver (number per enclosure)	2
	Midrange driver (diameter)	80.00 mm
	Midrange driver (material)	Paper, coated
	Woofer (number per enclosure)	2
	Woofer (diameter)	80.00 mm
	Woofer (material)	Paper, coated
	Enclosure material	Aluminium
	Enclosure surface	Brushed
	Wall mounting brackets	Yes
	Keyhole plate mounted	Yes
	Terminal clamps	Pole terminals, gold-plated
	Suitable for banana plug	Yes
	Maximum cable diameter	2.50 mm
	Suitable for AV receiver	Yes
<b>Dimensions</b>	Depth	9.60 cm
	Width	9.10 cm
	Height	46.50 cm
	Weight	2.50 kg

#### Subwoofer T 4000:

<b>Speaker</b>	Acoustic principle	1-Way-System
	Downfire	Yes
	Enclosure type	Bass reflex
	Maximum sound pressure level	102 dB/1m
	Frequency range from/to	35-200 Hz Hz
	Woofer (number per enclosure)	3
	Woofer (diameter)	130.00 mm
	Woofer (material)	Cellulose, coated
	Miscellaneous	Extreme stroke capability
	Enclosure material	MDF
	Enclosure surface	Matte lacquer
	Integrated stand	Yes
	Suitable for AV receiver	Yes

<b>Connections</b>	Cinch input stereo	1
<b>Electronics</b>	Lowest frequency (-3 dB)	35 Hz
	Input gain adjustment	Yes
	Frequency regulator (range)	Yes Hz
	Phase control	Yes
	Amplifier technology	Class-D
	Amplifier configuration	1.0
	Amplifier channels	1
	Power output capacity impulse (peak) Bass	240 W
	Power output capacity sinus (RMS) Bass	150 W
	Miscellaneous	DSP from analogue devices
	Power supply voltage	230 Volt volts
	Standby-Function	Yes
	Standby-Power consumption	0.40 watt
	Mains cable - IEC connector (non-heating device)	Yes
	Safety class	2
	Fuse	Yes
	Storage for settings when disconnected	Yes
	Automatic on/off	Yes
<b>Dimensions</b>	Depth	30.00 cm
	Width	95.50 cm
	Height	12.50 cm
	Weight	13.20 kg

#### RearStation Compact RX (pcs.):

<b>Speaker</b>	Terminal clamps	Loudspeaker terminals
	Maximum cable diameter	1.50 mm
<b>Connections</b>	Cinch input	1
<b>Electronics</b>	Amplifier technology	Class D
	Amplifier configuration	1.0
	Amplifier channels	1
	Power output capacity impulse (peak) Satellite	80 W
	Power output capacity sinus (RMS) Satellite	60 W
	Power supply voltage	230 volts
	Standby-Function	Yes
	Standby-Power consumption	0.40 watt
	Maximum power consumption	80 watt
	Storage for settings when disconnected	Yes
	Automatic on/off	Yes
	Miscellaneous	Crossover frequency: 2.4 GHz
<b>Dimensions</b>	Depth	4.20 cm
	Width	7.10 cm

Height	18.30 cm
Weight	0.30 kg