

Projection System	DLP Single 0.65" WXGA
Native Resolution	1280x800 pixels
Brightness (ANSI Lumens)	3,400 ANSI Lumens
Contrast Ratio	20,000:1
Display Color	1.07 Billion
Lens	F/#=2.6, f=6.9mm
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)
Throw Ratio	0.49
Image Size (Diagonal)	60" -120"
Zoom Ratio	Fixed
Keystone Adjustment	1D; Vertical ± 30 degrees
Projection Offset**	105%
Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200) * RB= Reduced blanking
Horizontal Frequency	15K -102KHz
Vertical Scan Rate	23-120Hz
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM
Weight	2.6 kg
Dimensions (W x H x D mm)	296*120*239 mm
Interface	HDMI x 2 (HDMI-2 share with MHL) PC In (D-sub 15pin) x 2 (share with component video) Monitor Out (D-sub 15pin) x 1 Composite Video In (RCA) x 1 S-Video In x 1 Audio In (mini jack) x 2 Audio L/R In (RCA) x 1 Audio Out (mini jack) x 1 LAN RJ45 x 1 (LAN control) RS232 (DB-9pin) x 1 USB (type A) x1 (power only 5V/1.5A) USB (type mini B) x 1 IR Receiver x2 (front, top)
Power Consumption	Typical 260W Network Standby<2W, Standby<0.5W
Audible Noise (Normal/Economic Mode)	33/29 dBA
Power Supply	AC100V to 240V, 50Hz to 60Hz
DMD type	DC3 DMD Chip
Light Source	Lamp (200W)
Light Source Life	5000/10000/10000/15000 hours (Normal/Eco/SmartEco/Lampsave mode)
Build in Speaker	10W x 1
Operating Temperature	0° ~ 40°C
Security	Kensington Lock, Security Bar
On-Screen Display Languages	Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian /Persian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Vietnam (30 languages)
Accessories (Standard)	Remote Control w/ Battery RCE013 x 1 Power Cord (by region) Quick Start Guide User Manual CD x 1 Warranty Card (by region)

#### Accessories (Optional)

Spare Lamp Kit 5JJGE05.001  
3D Glasses DGD5 5JJ9H25.002  
Document Camera S30 9HJ9L78.T3E  
PointWrite Kit PW02 5JJ9A26.12E  
PointWrite Touch Module PT12 5JJ8L26.13E  
Wall Mount 5JJ4R10.011

\*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

\*\*Offset is calculated by full screen height.