



Ready for action

Consono 35 Mk3

The Consono 35 Mk3 is a 5.1 home cinema set that delivers huge sound from a compact design. Experience movies and music in a whole new dimension with this high-performance system. A sleek design and distortion-free, high-powered sound put the Consono 35 Mk3 in a class of its own.

Highlights:

- Sets a new standard for affordability, reliability, and performance
- Visually and acoustically revamped satellites with robust metal grating
- Five identically constructed 2-way loudspeakers for a truly immersive sound experience
- Powerful subwoofer that can be used front- or down-firing, and wirelessly operated
- Centre speaker with excellent speech intelligibility even at low volume levels

Included components

- 1 x Centre Speaker CS 35 C Mk3
- 4 x Satellite-Speaker CS 35 FCR Mk3
- 1 x T 8 Subwoofer

Specifications

Satellite-Speaker CS 35 FCR Mk3:

| | | |
|-------------------|---|---------------------------------------|
| Speaker | Acoustic principle | 2-Way-System |
| | Enclosure type | Closed |
| | Continuous power handling (IEC - Long Term) | 80 Watt |
| | Peak power capacity (IEC - Short Term) | 160 Watt |
| | Sensitivity (2.83 V / 1 m) | 88 dB |
| | Minimum amplifier output power recommended | 10 Watt |
| | Maximum sound pressure level | 105 dB/1m |
| | Impedance | 4 - 8 Ohm |
| | Frequency range from/to | 150 - 20000 Hz |
| | Crossover frequency internal switch | 3400 Hz |
| | Crossover frequency to Woofer (recommended) | 150 - 180 Hz |
| | Miscellaneous | Neutral tuning |
| | Tweeter (number per enclosure) | 1 |
| | Tweeter (diameter) | 19.00 mm |
| | Tweeter (material) | Silk |
| | Midrange driver (number per enclosure) | 2 |
| | Midrange driver (diameter) | 80.00 mm |
| | Midrange driver (material) | Cellulose, coated |
| | Miscellaneous | High excursion drivers |
| | Enclosure material | Synthetic |
| | Enclosure surface | Impact-resistant lacquer, matte |
| | Net internal volume | 1.20 Litres |
| | Diameter of the stand screw threads | 6.00 mm |
| | Keyhole plate mounted | Yes |
| | Miscellaneous | Strong walls minimize resonances |
| | Maximum cable diameter | 2.50 mm |
| | Suitable for AV receiver | Yes |
| | Miscellaneous | requires little power for high levels |
| Dimensions | Depth | 9.50 cm |
| | Width | 10.00 cm |

| | |
|--------|----------|
| Height | 22.60 cm |
| Weight | 1.25 kg |

Centre Speaker CS 35 C Mk3:

| | | |
|-------------------|---|---------------------------------------|
| Speaker | Acoustic principle | 2-Way-System |
| | Enclosure type | Closed |
| | Continuous power handling (IEC - Long Term) | 80 Watt |
| | Peak power capacity (IEC - Short Term) | 160 Watt |
| | Sensitivity (2.83 V / 1 m) | 88 dB |
| | Minimum amplifier output power recommended | 10 Watt |
| | Maximum sound pressure level | 105 dB/1m |
| | Impedance | 4 - 8 Ohm |
| | Frequency range from/to | 150 - 20000 Hz |
| | Crossover frequency internal switch | 3400 Hz |
| | Crossover frequency to Woofer (recommended) | 150 - 180 Hz |
| | Tweeter (number per enclosure) | 1 |
| | Tweeter (diameter) | 19.00 mm |
| | Tweeter (material) | silk |
| | Midrange driver (number per enclosure) | 2 |
| | Midrange driver (diameter) | 80.00 mm |
| | Midrange driver (material) | coated cellulose |
| | Miscellaneous | high excursion driver |
| | Enclosure material | structure - synthetic |
| | Enclosure surface | impact-resistant lacquer, matte |
| | Net internal volume | 1.20 Litres |
| | Diameter of the stand screw threads | 6.00 mm |
| | Keyhole plate mounted | Yes |
| | Miscellaneous | strong walls minimize resonances |
| | Maximum cable diameter | 2.50 mm |
| | Suitable for AV receiver | Yes |
| | Miscellaneous | requires little power for high levels |
| Dimensions | Depth | 9.50 cm |
| | Width | 22.60 cm |
| | Height | 10.00 cm |
| | Weight | 1.25 kg |

T 8 Subwoofer:

| | | |
|----------------|--------------------|--------------|
| Speaker | Acoustic principle | 1-Way-System |
| | Downfire | Yes |
| | Frontfire | Yes |

| | | |
|--------------------|---|---|
| | Enclosure type | Bass reflex |
| | Maximum sound pressure level | 111 dB/1m |
| | Frequency range from/to | 33-200 Hz Hz |
| | Woofer (number per enclosure) | 1 |
| | Woofer (diameter) | 200.00 mm |
| | Woofer (material) | Aluminium |
| | Enclosure type | Bass reflex, DPU |
| | Enclosure material | MDF |
| | Enclosure surface | Matte coated |
| | Equalisation openings | 1 |
| | Integrated stand | Yes |
| | Miscellaneous | Reflection channel in DPU technology avoids flow noises, stable MDF housing structure with internal bracing |
| | Suitable for AV receiver | Yes |
| Connections | Cinch input | 1 |
| | Miscellaneous | Suitable for installation directly on the wall |
| Electronics | Miscellaneous | Can be wirelessly controlled |
| | Lowest frequency (-3 dB) | 37 Hz |
| | Bass boost/EQ | Yes |
| | Input gain adjustment | Yes |
| | Frequency regulator (range) | 37 - 200 Hz Hz |
| | Level control | Yes |
| | Phase control | Yes |
| | Miscellaneous | Can be used either front- or down-firing |
| | Amplifier technology | Class-D |
| | Amplifier configuration | 1.0 |
| | Amplifier channels | 1 |
| | Power output capacity impulse (peak) Bass | 100 W |
| | Power supply voltage | 230 Volt volts |
| | Standby-Function | Yes |
| | Standby-Power consumption | 1 watt |
| | Maximum power consumption | 100 watt |
| | Mains lead fixed | Yes |
| | Safety class | 2 |
| | Fuse | Yes |
| | Storage for settings when disconnected | Yes |
| | Automatic on/off | Yes |
| Dimensions | Depth | 38.00 cm |
| | Width | 31.10 cm |

| | |
|--------|----------|
| Height | 42.30 cm |
| Weight | 11 kg |