



## Ready for action

### Consono 35 Complete

We made our bestselling compact home cinema system even better: The same big 5.1 sound with movies, games and music is now available as a plug-&-play system with new features and the best price/performance ratio in its class.

#### Highlights:

- Powerful, high-definition sound with music, movies & games
- Plug-&-play 5.1 complete system with A/V receiver and compact hi-fi satellites
- Sophisticated hi-fi satellites feature protective metal grilles with attractive chrome accents
- 5 identical 2-way speakers with 2 midrange drivers each create highly realistic, room-filling sound
- Powerful but precise downfire subwoofer with the largest bass driver in this price class

## Included components

- 1 x Centre Speaker CS 35 C Mk3
- 4 x Satellite-Speaker CS 35 FCR Mk3
- 1 x T 6 Subwoofer
- 1 x CoreStation
- 1 x power cable
- 1 x Remote Control for Corestation
- 1 x 30m Speaker Cable 1.0mm<sup>2</sup> - C1030S
- 1 x HDMI-Cable 1.4 1.5m - C1515V

## Specifications

### CoreStation:

<b>Connections</b>	Bluetooth aptX	Yes
	Bluetooth	Yes
	Bluetooth	4.0 with aptX
	Digital inputs coaxial	1
	Digital inputs optical	2
	Cinch input	1
	Stereo jack 3.5mm - in	2
	High level speaker outputs	5
	Headphone output 3,5mm	1
	Video inputs- HDMI	4
	HDMI Version	1.4a (3D)
	Video outputs - HDMI	1
	Video outputs - HDMI	Yes
	HDMI Version	1.4a (3D)
	Miscellaneous	USB port for software updates
<b>Playback</b>	Dolby Digital	Yes
	DTS	Yes
	Dolby Pro Logic II	Yes
	Dolby Pro Logic II	Music, movies
<b>Radio</b>	Radio present	Yes
	Channel memory slot - FM	30
	FM - UKW	Yes
<b>Electronics</b>	Amplifier technology	Class-D
	Amplifier configuration	5.0
	Amplifier channels	5
	Power output capacity impulse (peak) Satellite	100 W
	Power output capacity sinus (RMS) Satellite	80 W
	Performance measured by (Ohm)	4

	Miscellaneous	30 Watt/Rear
	Power supply voltage	230 Volt volts
	Standby-Function	Yes
	Standby-Power consumption	0.40 watt
	Maximum power consumption	500 watt
	Mains cable - IEC connector (non-heating device)	Yes
	Safety class	2
	Storage for settings when disconnected	Yes
	Miscellaneous	Automatic off
	Integrated DSP	Yes
	Integrated DD/dts/PLII-Decoder	Yes
	Remote control	Radio
	Materials	Aluminium
	Presets	Yes
<b>Dimensions</b>	Depth	24.00 cm
	Width	30.80 cm
	Height	6.30 cm
	Weight	3.40 kg

#### Satellite-Speaker CS 35 FCR Mk3:

<b>Speaker</b>	Acoustic principle	2-Way-System
	Enclosure type	Closed
	Continuous power handling (IEC - Long Term)	80 Watt
	Peak power capacity (IEC - Short Term)	160 Watt
	Sensitivity (2.83 V / 1 m)	88 dB
	Minimum amplifier output power recommended	10 Watt
	Maximum sound pressure level	105 dB/1m
	Impedance	4 - 8 Ohm
	Frequency range from/to	150 - 20000 Hz
	Crossover frequency internal switch	3400 Hz
	Crossover frequency to Woofer (recommended)	150 - 180 Hz
	Miscellaneous	Neutral tuning
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	19.00 mm
	Tweeter (material)	Silk
	Midrange driver (number per enclosure)	2
	Midrange driver (diameter)	80.00 mm
	Midrange driver (material)	Cellulose, coated
	Miscellaneous	High excursion drivers
	Enclosure material	Synthetic
Enclosure surface	Impact-resistant lacquer, matte	

	Net internal volume	1.20 Litres
	Diameter of the stand screw threads	6.00 mm
	Keyhole plate mounted	Yes
	Miscellaneous	Strong walls minimize resonances
	Maximum cable diameter	2.50 mm
	Suitable for AV receiver	Yes
	Miscellaneous	requires little power for high levels
<b>Dimensions</b>	Depth	9.50 cm
	Width	10.00 cm
	Height	22.60 cm
	Weight	1.25 kg

### Centre Speaker CS 35 C Mk3:

<b>Speaker</b>	Acoustic principle	2-Way-System
	Enclosure type	Closed
	Continuous power handling (IEC - Long Term)	80 Watt
	Peak power capacity (IEC - Short Term)	160 Watt
	Sensitivity (2.83 V / 1 m)	88 dB
	Minimum amplifier output power recommended	10 Watt
	Maximum sound pressure level	105 dB/1m
	Impedance	4 - 8 Ohm
	Frequency range from/to	150 - 20000 Hz
	Crossover frequency internal switch	3400 Hz
	Crossover frequency to Woofer (recommended)	150 - 180 Hz
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	19.00 mm
	Tweeter (material)	silk
	Midrange driver (number per enclosure)	2
	Midrange driver (diameter)	80.00 mm
	Midrange driver (material)	coated cellulose
	Miscellaneous	high excursion driver
	Enclosure material	structure - synthetic
	Enclosure surface	impact-resistant lacquer, matte
	Net internal volume	1.20 Litres
	Diameter of the stand screw threads	6.00 mm
	Keyhole plate mounted	Yes
	Miscellaneous	strong walls minimize resonances
	Maximum cable diameter	2.50 mm
	Suitable for AV receiver	Yes
	Miscellaneous	requires little power for high

<b>Dimensions</b>	Depth	levels 9.50 cm
	Width	22.60 cm
	Height	10.00 cm
	Weight	1.25 kg

**T 6 Subwoofer:**

<b>Speaker</b>	Acoustic principle	1-Way-System
	Downfire	Yes
	Enclosure type	Bass reflex
	Maximum sound pressure level	104 dB/1m
	Frequency range from/to	33 - 200 Hz Hz
	Woofer (number per enclosure)	1
	Woofer (diameter)	165.00 mm
	Woofer (material)	Coated cellulose
	Enclosure type	Bass reflex
	Enclosure material	MDF
	Enclosure surface	Matte laminate
	Equalisation openings	1
	Equalisation openings (pos.)	Bottom
	Net internal volume	20 Litres
	Integrated stand	Yes
	<b>Connections</b>	Miscellaneous
<b>Electronics</b>	Lowest frequency (-3 dB)	33 Hz
	Amplifier technology	Class-D
	Amplifier channels	1
	Power output capacity impulse (peak) Bass	90 W
	Power output capacity sinus (RMS) Bass	60 W
	Power supply voltage	230 Volt volts
	Standby-Function	Yes
	Standby-Power consumption	0.40 watt
	Maximum power consumption	120 watt
	Safety class	2
	Automatic on/off	Yes
<b>Dimensions</b>	Depth	38.00 cm
	Width	21.00 cm
	Height	40.00 cm
	Weight	8.57 kg