VGA (800 x 600) 300AL 3000:1 07 Billion Colors =2.56-2.68, f=22.04-24.14 mm ative 4:3 (5 aspect ratio selectable) 96-2.15 (78"@3.1m) 0"~300" 1:1 90W 500/6000/6500/10000 hours D, Vertical +/- 40 degrees 20% ±5% GA(640 x 480) to WUXGA_RB(1920X1200) *RB=Reduced blanking
3000:1 07 Billion Colors =2.56-2.68, f=22.04-24.14 mm ative 4:3 (5 aspect ratio selectable) 96-2.15 (78"@3.1m) 0"~300" 1:1 90W 500/6000/6500/10000 hours D, Vertical +/- 40 degrees 20% ±5%
07 Billion Colors =2.56-2.68, f=22.04-24.14 mm ative 4:3 (5 aspect ratio selectable) 96-2.15 (78"@3.1m) 0"~300" 1:1 90W 500/6000/6500/10000 hours D, Vertical +/- 40 degrees 20% ±5%
=2.56-2.68, f=22.04-24.14 mm ative 4:3 (5 aspect ratio selectable) 96-2.15 (78"@3.1m) 0"~300" 1:1 90W 500/6000/6500/10000 hours D, Vertical +/- 40 degrees 20% ±5%
ative 4:3 (5 aspect ratio selectable) 96-2.15 (78"@3.1m) 0"~300" 1:1 90W 500/6000/6500/10000 hours D, Vertical +/- 40 degrees 20% ±5%
96-2.15 (78"@3.1m) 0"~300" 1:1 90W 500/6000/6500/10000 hours D, Vertical +/- 40 degrees 20% ±5%
0"~300" 1:1 90W 500/6000/6500/10000 hours D, Vertical +/- 40 degrees 20% ±5%
1:1 90W 500/6000/6500/10000 hours D, Vertical +/- 40 degrees 20% ±5%
90W 500/6000/6500/10000 hours D, Vertical +/- 40 degrees 20% ±5%
500/6000/6500/10000 hours D, Vertical +/- 40 degrees 20% ±5%
D, Vertical +/- 40 degrees 20% ±5%
20% ±5%
GA(640 x 480) to WUXGA_RB(1920X1200) *RB=Reduced blanking
5~102KHz
3~120Hz
80i, 480p, 576i, 576p, 720p, 1080i, 1080p
TSC, PAL, SECAM
omputer in (D-sub 15pin) x 2 (Share with component) lonitor out (D-sub 15pin) x 1 omposite Video in (RCA) x 1 -Video in (Mini DIN 4pin) x 1 DMI x 1 udio in (Mini Jack) x 1 udio out (Mini Jack) x 1 peaker 2W x 1 SB (Type mini B) x 1 S (Receiver x 1 (Front)
33 x 95 x 222 mm (with feet) 33 x 88.7 x 222 mm (without feet)
9kg
3/28 dBA (Normal/Economic mode)
C100 to 240 V, 50 to 60 Hz
ormal 270W, Eco 220W, Standby<0.5W
rame Sequential: Up to 720p rame Packing: Up to1080p ide by Side: Up to 1080i/p op Bottom: Up to 1080p
rabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ indi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ omanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese & Languages)
ynamic/Presentation/sRGB/Cinema/(3D)/User 1/User 2
emote Control w/ Battery ower Cord (by region) ownloading UM and Regulatory Statements uick Start Guide /arranty Card (by region)
L'Euupss S 3 S S S S S S S S S S S S S S S S S

Accessories (Optional)	Ceilling Mount 3D Glasses Carry bag
Environmental Notice	Lamp in this product contains mercury. To dispose of the product or used lamps, consult your local environment authorities for regulations or see www.lamprecycle.org.