## **Key Features**

[ Amazing Color Performance ] | Best in Class Color Accuracy | Fine-tuned Viewing Experience | [ Professional Applications ] | Higher Brightness



## Product **Description**

Equipped with stacking and 360-degree projection, the Pro9530HDL offers versatile projection capabilities to fit professional and creative application requirements. Pro9530HDL's centered lens boasts 5,200 lumens and Full HD resolution, with multiple adjustment options for horizontal & vertical lens shift, 1.7x optical zoom, HV keystone, 4-corner, and 12V trigger, offering flexible and easy installation. To ensure its reliability, features such as an advanced sealed optical engine, wire-netting-covered lamp, and waveform air filter make it more durable and safeguard it against damage caused by regular usage. Powered by SuperColor<sup>TM</sup>, it provides amazing colors and great contrast for images while utilizing auto power on, cell phone remote control (With vRemote app), and network management features for easy management. The Pro9530HDL is the ideal projector for commercial installations and large venues.

Visit Us

www.viewsonic.com

PRODUCT SPECIFICATION	
Resolution:	1920x1080
Brightness (ANSI Lumens):	5200lm
Contrast (Max.):	6000:1
Lamp Hour (Normal / Eco):	1500hrs / 3500hrs
Throw Ratio in Meters (Wide ~ Tele):	1.25~2.13
Lens Shift:	Yes
Optical Zoom:	1.7x
Digital Zoom:	0.8x~2.0x
Screen Size:	25.4"~361.4"
Projection Offset:	118%~135.9%
Display Colours:	1.07 Billion Colors (30 bits per color)
Keystone:	HV
Noise min (Eco):	31 dB
Speaker:	7W x2
INPUT CONNECTIVITY	
HDMI/MHL:	1
HDMI In:	1
VGA-in:	2
Component Input:	2 (Share with VGA-in)
S-Video:	1
Composite Input:	1
Audio-in (3.5mm):	3
Audio-in (RCA pair):	1
USB Type A:	1 (Only charging)
USB Type B:	N/A
Mini USB:	1 (Service)
Micro USB cable:	N/A
Microphone in (3.5mm):	1
SD Card reader:	N/A
BNC:	1
Wire Remote in:	1
DVI-D:	1
OUTPUT CONNECTIVITY	
VGA-out:	1
Audio-out (3.5mm):	1
Audio-out (RCA pair):	1
Wire Remote out:	1
CONTROL	
RS232 (9 pin):	1
Network Mangment (LAN cable):	1
12V Power Trigger:	1
3D VESA:	1

N/A

IR Connector:

## DIMENSIONS AND POWER

DIMENSIONS AND POWER	
Dimension (WxDxH):	445 mm(W) x 325.5 mm(D) x147.8 mm(H) 17.51" (W) x 12.81 " (D) x 5.82" (H)
Net Weight:	8.29 kg (18.26 lb)
Power Source:	100~240Vac 50/60Hz
Power Consumption:	480W (Typ.)
SUPPLIED ACCESSORIES	
Power cord:	1
VGA cable:	1
HDMI cable:	N/A
Remote Control (with batteries):	1
Cable cover:	N/A
Quick Start Guide & CD:	1
LANGUAGES	
On Screen Display:	Total 27 languages
REGULATIONS	
Standard:	Mexico Energy FCC / CE / EMC CB / CCC ROHS / REACH / SVHC / WEEE / ErP Mexico NOM / UL / CUL / PSB / RCM