PJ X2340/PJ S2340

GENERAL

Lamp life:

Projection system: Single chip DI P

PJ S2340: 480,000 (800 x 600 pixels) Resolution:

PJ X2340: 786,432 (1,024 x 768

pixels)

Panel: Panel size: 0.55 inch Aspect ratio: 4:3 3,000 lumen Brightness:

1,073,000,000 colours Colour reproducibility:

Contrast ratio: 2.200:1 High contrast ratio: 10.000:1 Projection screen size: 30" to 300'

Projection distance: 1.2 to 13.1 m (from rear of unit to

projection surface)

Lamp High-pressure mercury lamp: standard:

190 W, Eco mode: 160 W Standard: 4,500 hours Eco mode: 6,000 hours

RGB compatible signals : Real display: SVGA (800 x 600), VGA

(640 x 480), PJ X2340: XGA (1,024 x

Compressed representation: UXGA (1,600 x 1,200), SXGA (1,280 x 1,024), WXGA (1,280 x 800), XGA (1,024 x

768)

Input signals: NTSC PAL

SECAM NTSC4.43 PAL-M PAL-60 50 Hz (mono) 60 Hz (mono)

Analogue RGB compatible Horizontal: 15 - 91.1 kHz Vertical: 24 - 85 Hz scanning frequency:

Zoom ratio: 1.1 Zoom Manual Focus: Manual

Mini D-SUB15pin x 1 (Computer IN) Connection terminal: Mini D-SUB15pin x 1 (Monitor OUT)

RCA_1pin x 1 (Video) Mini Jack x 1 (Audio1 IN/OUT) HDMI x 1

RS-232C 3-pin x 1 (service)

Primary features: Mute (Blank)

Re-size (Magnify) Password protection Eco mode 3D ready Kensington lock 2 W mono

Built-in speaker: Dimensions (W x D x H): 286 x 100 x 208 mm

Weight: 2.4 kg 100 - 240 V, 50/60 Hz Power source:

ECOLOGY

Power consumption: Operating power: 273 W

Energy Saver mode: 210 W Stand-by mode: 0.5 W

5°C - 40°C Operating temperature: Operating humidity: 20% - 80%

Temperature: -20°C - 60°C Storage conditions: Humidity: 20% - 80%

ACCESSORIES

Read this first / Manual (Starting Guide), RGB cable, Power cable, CD-ROM and manual, Remote control with batteries, Lens cap

CONSUMABLES

Replacement lamp Type 26

For availability of models, options and software, please consult your local Ricoh supplier.



www.ricoh-europe.com

ISO9001 certified ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2016 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.