

T 10 Subwoofer

High-class active subwoofer, can be used either front- or down-firing



Speaker

Acoustic principle	1-Way-System
--------------------	--------------

Downfire	Yes
----------	-----

Frontfire	Yes
-----------	-----

Enclosure type	Bass reflex
----------------	-------------

Maximum sound pressure level	115 dB/1m
------------------------------	-----------

Frequency range from/to	37 - 200 Hz Hz
-------------------------	----------------

Woofers (number per enclosure)	1
--------------------------------	---

Woofers (diameter)	250.00 mm
--------------------	-----------

Woofers (material)	Aluminium
--------------------	-----------

Enclosure material	MDF
--------------------	-----

Enclosure surface	Matte coated
-------------------	--------------

Equalisation openings	1
-----------------------	---

Integrated stand	Yes
------------------	-----

Miscellaneous	Reflection channel in DPU technology avoids flow noises, stable MDF housing structure with internal bracing
---------------	---

Suitable for AV receiver	Yes
--------------------------	-----

Connections

Cinch input	1
-------------	---

Electronics

Lowest frequency (-3 dB)	33 Hz
--------------------------	-------

Bass boost/EQ	Yes
---------------	-----

Input gain adjustment	Yes
-----------------------	-----

Level control	Yes
---------------	-----

Phase control	Yes
---------------	-----

Miscellaneous	Can be used either front- or down-firing
---------------	--

Amplifier technology	Class-D
----------------------	---------

Amplifier configuration	1.0
-------------------------	-----

Amplifier channels	1
--------------------	---

Power output capacity impulse (peak) Bass	150 W
--	-------

Power supply voltage	230 Volt volts
----------------------	----------------

Standby-Function	Yes
------------------	-----

Standby-Power consumption	1 watt
Maximum power consumption	150 watt
Mains lead fixed	Yes
Safety class	2
Fuse	Yes
Storage for settings when disconnected	Yes
Automatic on/off	Yes
Miscellaneous	Wireless subwoofer module integrated (subwoofer with compatible feeders can be controlled wirelessly)
Dimensions	
Depth	38.00 cm
Width	35.10 cm
Height	48.30 cm
Weight	15.60 kg